

Material Safety Data Sheet

718 Sto BTS-NC

Section I - Manufacturer's Information

Identity: **Sto BTS-NC**

Common Name/Synonym: **Polymer Modified Cementitious Based Groundcoat/Adhesive**

Manufacturer's Name: **Sto Corp.**
6175 Riverside Drive, SW
Atlanta, GA 30331

Information #: **(404) 346-3666**
Emergency #: **(800) 424-9300**

DOT Hazardous Class: **Not Regulated**
CAS Number: **Not Registered**

Section II - Preparation Information

Prepared By: **Sto Corp. Research and Development Department**

Date Prepared: **27-Jul-01**

Section III - Hazardous Ingredients

Component - A Ingredient	Percent w/w	CAS Number	OSHA	TWA/TLV ACGIH	Other	LD50	LC50
Antimony Trioxide	1-5	1309-64-4	N/E mg/m ³	N/E mg/m ³	N/E mg/m ³	N/E	N/E
Silicon Dioxide	60-100	14808-60-7	10/(%SiO ₂ +2) mg/m ³	0.10 mg/m ³	NIOSH 0.05 mg/m ³	N/E	N/E

This product contains a chemical known to the State of California to cause cancer.

Section IV - Physical/Chemical Characteristics

Boiling Point: N/A	Vapor Density [Air=1]: N/A	Vapor Pressure: N/A	pH Level: >12
Melting Point: N/A	Evaporation Rate [Ether=1]: N/E	Physical State: solid	Solubility in Water: miscible
Freezing Point: N/A	Specific Gravity: [H ₂ O=1]: >1	Odor Threshold: N/E	Coefficient of Water/Oil Distribution: N/A
Appearance and Odor: grey powder			

Section V - Fire and Explosion Hazard Data

Component - A	Flash Point: N/A	Autoignition Temperature: N/E
Flammability: N/E	Sensitivity to impact: None	Sensitivity to Static Discharge: None
Limits LEL/UEL: N/E - N/E		
Hazardous Decomposition Products: COx, smoke	Special Firefighting Procedures: SCBA, full protective gear	
Unusual Fire and Explosive Hazards: None	Extinguishing Media: Water spray, foam, dry chemical	

Section VI - Reactivity Data

Component - A	Stability: Stable	Incompatibility (Materials to Avoid): None
Hazardous Decomposition Products: None		Conditions to Avoid: None
Hazardous Polymerization: Will not occur		

Section VII - Health Hazard Data

Carcinogenicity: Yes	NTP: Yes	IARC: Grp. 1	OSHA Regulated: No	LD50: N/A	LC50: N/A
Effects and Hazards of Eye Contact: Direct contact with material may cause irritation.					
Effects and Hazards of Inhalation (Breathing): Product contains silica (quartz) dust, which has been designated by IARC as a group 1 - human carcinogen. Prolonged exposure to respirable silica (quartz) dust may cause delayed (chronic) lung injury such as silicosis.					
Effects and Hazards of Skin Contact: Contact with skin may cause reddening or a slight rash in individuals with sensitive skin.					
Effects and Hazards of Ingestion (Swallowing): May cause some stomach distress.					

Section VIII - Emergency and First Aid Procedures

Material Safety Data Sheet

718 Sto BTS-NC

Treatment for Eye Contact:

As with any foreign material in the eyes, they should be flushed for fifteen minutes with running water while holding the eyes open. This will assist in flushing material from the eye. If irritation continues, seek medical attention.

Treatment for Inhalation
(Breathing):

If respiratory irritation occurs, go to fresh air. Flood work area with fresh air and if irritation continues, seek medical attention.

Treatment for Skin

Contact:

Wash with mild soap and water. Hand creams should be used to prevent dry skin. If skin irritation, reddening or a rash occur, seek medical attention.

Treatment for Ingestion
(Swallowing):

Contact medical help immediately; untrained first aid personnel should not attempt to administer first aid.

Section IX - Precautions for Safe Handling and Use

Steps to be taken in case
material is released or
spilled (Dry Stage):

Sweep and dispose of in proper receptacle.

Steps to be taken in case
material is released or
spilled (Wet Stage):

Scoop into proper receptacle and allow to harden.

Waste Disposal
Method:

Per local, state and federal regulations.

Precautions To Be Taken In
Handling and Storing:

Store in a cool dry location, out of direct sunlight.

Other Precautions:

This material is an industrial product designed to be used by professionals familiar with the requirements of this MSDS.

Respiratory Protection:

Respiratory protection is recommended for mixing this product. Respiratory protection is not required for normal use of this product. When material is mixed, ground upon or sanded when it is dry, NIOSH/MSHA approved respirators for silica (quartz) dust should be provided and worn. All workers required to use respiratory protection should be trained in their proper selection, use and care.

Ventilation:

Recommended; local or mechanical when mixing, applying or sanding the product in the dry state.

Protective Gloves:

Recommended; plastic or rubber.

Eye Protection:

Recommended; chemical splash safety goggles.

Other Protective
Equipment:

Recommended; splash bib and protective clothing.

Work and Hygienic
Practices:

Remove and wash contaminated clothing. As with all commercial and industrial products, always wash hands before eating or smoking.

California Proposition 65:

This product contains crystalline silica (quartz sand), which is considered a carcinogen by the State of California.

The information and recommendations contained herein are, to the best of Sto Corp.'s knowledge and belief, accurate and reliable as of the date issued. Sto Corp. does not warrant or guarantee their accuracy or reliability, and Sto Corp. shall not be liable for any loss or damage arising out of their use thereof. The information and recommendations are offered for the users' consideration and examination, and it is the users' responsibility to satisfy itself that they are suitable and complete for its particular use.