


StoPowerwall™ NExT Pan Flashing Installation

Detail No.: 4.24c E

Date: February 2009



Notes:

- 1] StoGuard™ Waterproofing/ Air Barrier should be installed as part of an air tight assembly.
- 2] To restrict air movement under or around the pan flashing, set the pan flashing into a wet sealant gasket. The sealant must be compatible with the flashing and StoGuard™ materials.
- 3] The window or other object being installed in the opening should be sealed on the interior side between the object and the StoGuard™/pan flashing assembly. Any intruding moisture should be directed to the pan flashing and out of the assembly beyond the finish face of the cladding. (Refer to Sto detail 4.22E)

Attention

Sto products are intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. They should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all, and assumes no, liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, or for other construction activities beyond Sto's control. Improper use of Sto products or use as part of an improperly designed or constructed larger assembly or building may result in serious damage to Sto products, and to the structure of the building or its components. **STO CORP. DISCLAIMS ALL WARRANTIES EXPRESS OR IMPLIED EXCEPT FOR EXPLICIT LIMITED WRITTEN WARRANTIES ISSUED TO AND ACCEPTED BY BUILDING OWNERS IN ACCORDANCE WITH STO'S WARRANTY PROGRAMS WHICH ARE SUBJECT TO CHANGE FROM TIME TO TIME.** For the fullest, most current information on proper application, clean-up, mixing and other specifications and warranties, cautions and disclaimers, please refer to the Sto Corp. website, www.stocorp.com.

www.stocorp.com