




# StoPowerwall™ Stucco Systems with Structalath Twin Trac Reinforcement

<b>Systems Comparison Chart</b>	<b>StoPowerwall NExT with Structalath Twin Trac</b>	<b>StoPowerwall with Structalath Twin Trac</b>	<b>Generic 3 Coat stucco system</b>
			
<b>Stucco System Warranty</b>	<b>6 to 12 yrs</b>	<b>1 to 7 yrs</b>	<b>None</b>
- Includes StoGuard fluid-applied membrane	<b>Yes</b>	<b>No</b>	<b>No</b>
- Includes Structalath Twin Trac	<b>Yes</b>	<b>Yes</b>	<b>No</b>
- Includes StoPowerwall stucco	<b>Yes</b>	<b>Yes</b>	<b>No</b>
- Includes Sto Primers and Finishes	<b>Yes</b>	<b>Yes</b>	<b>No</b>
<b>StoGuard® Fluid-applied Membrane</b>			
- A fluid-applied air and moisture barrier that is waterproof, seamless & structural.	<b>Yes</b>	<b>No</b>	<b>No</b>
- A qualified CMCC listed air barrier that can provide energy savings between 10% to 40% when properly installed in tandem with other air barrier components	<b>Yes</b>	<b>No</b>	<b>No</b>
<b>Structalath Twin Trac</b>			
- ICC code recognition	<b>Yes</b>	<b>Yes</b>	<b>Yes</b>
- Up to 30% labor savings on lath installation	<b>Yes</b>	<b>Yes</b>	<b>No</b>
- ¼" flat bottom furring facilitates application for uniform stucco thickness and proper embedding of wire in the stucco	<b>Yes</b>	<b>Yes</b>	<b>No</b>
<b>StoPowerwall Stucco</b>			
- ICC code approval	<b>Yes</b>	<b>Yes</b>	<b>Yes</b>
- Stucco mix control in ISO 9001:2000 manufacturing facilities	<b>Yes</b>	<b>Yes</b>	<b>No</b>
- Reduced thickness, which results in reduced dead loads on the structure	<b>Yes</b>	<b>Yes</b>	<b>No</b>