



June 14, 2006

Sto Corp.
6175 Riverside Drive, S.W.
Atlanta, Georgia 30331
Phone: (404) 346-3666
Fax: (404) 346-7422
www.stocorp.com

To: Whom It May Concern

From: Terry L. Viness, P.E.
Senior Technical Services Manager
Sto Corp.

Re: Use of Easy Spred™ Pumping Aid in Sto Powerwall® Stucco

This confirms that Sto Corp. recommends using Easy Spred™ pumping aid when applying Sto Powerwall® stucco using the Sto All Purpose Stucco Pump.

Sto Corp. has tested Sto Powerwall® Stucco with Easy Spred® and determined that Easy Spred® does not adversely affect the physical properties of the stucco when it is properly proportioned, mixed, placed and cured. Laboratory testing that was performed by Sto is summarized below:

Sto Powerwall® Stucco	Without Easy Spred™	With Easy Spred™
Sto Powerwall, lbs	240	240
Sand, lbs	600	600
Water, lbs	125	125
Easy Spred™, lbs	0	7
Unit weight, pcf	125.6	125.5
Compressive Strength at 28 days, psi	1982	1894
Length Change at 28 days, percent	-0.11	-0.15

Easy Spred™ is added at a rate of 2.3 lbs per 80-lb bag of Sto Powerwall® Stucco or approximately 2.9%. Mixing and spraying instructions are attached for your use.

The proper use of Easy Spred™ will not change the warranty offered for the Sto Powerwall® system.