

# Sto All Purpose Stucco Pump



Features	Benefits
Versatile, spray application of Powerwall® Stucco, BTS, Leveler, Skim Coat, finishes, coatings and some mortars	Reduces application time, one pump for the whole job or for many different types of jobs
Variable flow rate from 0 to 3.6 cu yd/hr; distances up to 210 feet	Adjustable application speed for the job; eliminates need for hauling buckets on to scaffolding or hassling with material in wheel barrows
Operates on single phase 220V Power	Readily available at most job sites
Reversible Pump	Safely reduces pressure in hose when needed
Easy to use, low maintenance	Little to no job downtime, saves money
Remote control On/Off at nozzle	Eliminates need to "man" the pump; facilitates smaller crew sizes, saves money
Various hose lengths available	Configure based on job requirements; eliminates bucket staging on scaffolding, saves money
Easy clean-up	Reduces time and labor, saves money
Compatible with Sto S-25 Continuous Mixer	Enables automated mixing and pumping of pre-mixed, "just add water" products like Sto Leveler and Sto adhesives/basecoats

Complete your stucco jobs faster and easier with the new **Sto All Purpose Stucco Pump**. This versatile new pump can spray Sto Powerwall® Stucco, as well as most other Sto materials, making it the "do all" pump on the job.

The **Sto All Purpose Stucco Pump** is a variable speed rotor/stator pump that sprays stucco at rates of 0 to 2.8 cu yd/hr at distances up to 210 feet. It operates on single phase 220V power, readily available at most job sites.

In addition, the **Sto All Purpose Stucco Pump** is backed by Sto's superior service, support and training. Through our toll-free HelpLine or by physically being on the job, StoMachine Technology will assist you and your crew in taking full advantage of the benefits of the equipment.

Contact your local distributor for more information.  
Please visit us at [www.stocorp.com](http://www.stocorp.com) or call us toll-free at 800-221-2379.



# Maximize Your Bottom Line With StoMachine Technology

Sto is committed to helping contractors maximize their business potential. By developing advanced application technologies that are designed to work with Sto products, and by providing unmatched levels of field support and training for both the product and the equipment, StoMachine Technology enables contractors to do more work, faster, without compromising quality.



“Our business was being squeezed by low cost competitors performing substandard work. Once we received the Sto All Purpose Stucco Pump, we were able to perform more jobs, faster, without adding more labor. This effectively lowered our overhead cost per project, and has enabled us to offer high quality workmanship at extremely competitive prices. Those low cost competitors can’t keep up!”

– Applewood Drywall, Waukesha, WI



## Contact Sto Corp.

For more information on how StoMachine Technology can help you complete more jobs faster, contact Sto Corp., toll-free at 1-800-221-2397 or your local Sto distributor. If you have operational or technical questions on any of the StoMachine Technology programs or equipment, please call the [StoMachine Technology HelpLine at 1-888-522-0184](tel:1-888-522-0184), available 8:00 AM – 5:00 PM EST.

### Sto All Purpose Stucco Pump Specifications

Overall Height	37"
Stucco Hopper Height	23"
Finish Hopper Height	31.5"
Width	78"
w/o Stucco Hopper	33"
Length	74"
w/o Rotor/Stator	49"
Weight	495 lbs
w/ Stucco Hopper	605 lbs
w/ Finish Hopper	542 lbs
Power	220V Single-Phase
Output	0 - 3.6 cu yd/hr; 0 - 9.5 gpm
Stucco Hopper Capacity	0.27 cu yd;
	55 gallons
Standard Hopper Capacity	30 gallons

#### ATTENTION

Sto products are intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. They should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all, and assumes no, liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, or for other construction activities beyond Sto's control. Improper use of Sto products or use as part of an improperly designed or constructed larger assembly or building may result in serious damage to this product, and to the structure of the building or its components. **STO CORP. DISCLAIMS ALL WARRANTIES EXPRESS OR IMPLIED EXCEPT FOR EXPLICIT LIMITED WRITTEN WARRANTIES ISSUED TO AND ACCEPTED BY BUILDING OWNERS IN ACCORDANCE WITH STO'S WARRANTY PROGRAMS WHICH ARE SUBJECT TO CHANGE FROM TIME TO TIME.** For the fullest, most current information on proper application, clean-up, mixing and other specifications and warranties, cautions and disclaimers, please refer to the Sto Corp. website, [www.stocorp.com](http://www.stocorp.com).



[www.stocorp.com](http://www.stocorp.com)

5772 07/07 VEN 6409

