

Material Safety Data Sheet

CR246 Sto Bonding and Anti-Corrosion Agent

Section I - Manufacturer's Information

Identity: **Sto Bonding and Anti-Corrosion Agent** Common Name/Synonym: **Acrylic, Cement, Epoxy-Based Bonding Agent**
Manufacturer's Name: **Sto Corp.** Information #: **(404) 346-3666** DOT Hazardous Class: **Not Registered**
Name: **6175 Riverside Drive, SW** Emergency #: **(800) 424-9300** CAS Number: **Not Registered**
Atlanta, GA 30331

Section II - Preparation Information

Prepared By: **Sto Corp. Research and Development Department** Date Prepared: **18-May-05**

Section III - Hazardous Ingredients

Component - A Ingredient	Percent w/w	CAS Number	OSHA	TWA/TLV ACGIH	Other	LD50	LC50
-----------------------------	----------------	------------	------	------------------	-------	------	------

No Reportable Hazardous Ingredients. Product is Water-Based

Component - B Ingredient	Percent w/w	CAS Number	OSHA	TWA/TLV ACGIH	Other	LD50	LC50
Barium Metaborate Monohydrate	1-5	13701-59-2	0.5 mg/m ³	0.5 mg/m ³	N/E mg/m ³	N/E	N/E
Portland Cement	10-30	65997-15-1	5.0 mg/m ³	10.0 mg/m ³	N/E mg/m ³	N/E	N/E
Silicon Dioxide	60-100	14808-60-7	10/(%SiO ₂ +2) mg/m ³	0.10 mg/m ³	NIOSH 0.05 mg/m ³	N/E	N/E
Silica - Amorphous	1-5	112945-525	10/(%SiO ₂ +2) mg/m ³	10.0 mg/m ³	N/E mg/m ³	N/E	N/E

Section IV - Physical/Chemical Characteristics

Component - A
Boiling Point: **100 deg C/212 deg F** Vapor Density [Air=1]: **>1** Vapor Pressure: **N/E** pH Level: **7.0 - 10.0**
Melting Point: **N/A** Evaporation Rate [Ether=1]: **<1** Physical State: **Liquid** Solubility in Water: **Miscible**
Freezing Point: **N/A** Specific Gravity: [H₂O=1]: **>1.0** Odor Threshold: **N/E**
Appearance and Odor: **White Liquid - Mild Odor** Coefficient of Water/Oil Distribution: **N/E**

Component - B
Boiling Point: **N/A** Vapor Density [Air=1]: **>1** Vapor Pressure: **N/A** pH Level: **N/A**
Melting Point: **N/A** Evaporation Rate [Ether=1]: **N/A** Physical State: **solid** Solubility in Water: **Slightly Soluble**
Freezing Point: **N/A** Specific Gravity: [H₂O=1]: **>1.0** Odor Threshold: **N/E**
Appearance and Odor: **Gray Powder -Slight Odor** Coefficient of Water/Oil Distribution: **N/E**

Section V - Fire and Explosion Hazard Data

Component - A
Flammability: **N/A** Flash Point: **N/A** Autoignition Temperature: **N/A**
Limits LEL/UEL: **N/A - N/A** Sensitivity to impact: **N/A** Sensitivity to Static Discharge: **N/E**
Hazardous Decomposition Products: **COx, NOx** Special Firefighting Procedures: **SCBA, full protective gear**
Unusual Fire and Explosive Hazards: **May emit toxic fumes under fire conditions.** Extinguishing Media: **Water spray, foam, dry chemical**

Component - B
Flammability: **N/A** Flash Point: **N/A** Autoignition Temperature: **N/A**
Limits LEL/UEL: **N/A - N/A** Sensitivity to impact: **N/A** Sensitivity to Static Discharge: **N/E**
Hazardous Decomposition Products: **COx, NOx** Special Firefighting Procedures: **SCBA, full protective gear**
Unusual Fire and Explosive Hazards: **May emit toxic fumes under fire conditions.** Extinguishing Media: **Water spray, foam, dry chemical**

Material Safety Data Sheet

CR246 Sto Bonding and Anti-Corrosion Agent

Component - A

Hazardous Decomposition Products: **COx, NOx**

Stability: **Stable**

Incompatibility (Materials to Avoid): **Strong Oxidizers, Strong Bases**

Hazardous Polymerization: **None**

Conditions to Avoid: **Fires when curing**

Component - B

Hazardous Decomposition Products: **COx, NOx**

Stability: **Stable**

Incompatibility (Materials to Avoid): **Strong Oxidizers, Strong Bases**

Hazardous Polymerization: **None**

Conditions to Avoid: **Fires when curing**

Section VII - Health Hazard Data

Carcinogenicity: **No** NTP: **No** IARC: OSHA Regulated: **No** LD50: **N/A** LC50: **N/A**

Effects and Hazards of

Eye Contact: **Direct contact with the material may cause irritation.**

Effects and Hazards of

Inhalation (Breathing): **Prolonged exposure to respirable silica (quartz) dust may cause delayed (chronic) lung injury.**

Effects and Hazards of

Skin Contact: **Contact with the skin may cause reddening or a slight rash in individuals with sensitive skin.**

Effects and Hazards of

Ingestion (Swallowing): **May cause some stomach distress.**

Section VIII - Emergency and First Aid Procedures

Treatment for Eye

Contact: **As with any foreign material in the eyes, they should be flushed for fifteen minutes with running water while holding the eyes open. This will assist in flushing material from the eye. If irritation continues, seek medical attention.**

Treatment for Inhalation

(Breathing): **If respiratory irritation occurs, go to fresh air. Flood work area with fresh air and if irritation continues, seek medical attention.**

Treatment for Skin

Contact: **Wash with mild soap and water. Hand creams should be used to prevent dry skin. If skin irritation, reddening or a rash occurs, seek medical attention.**

Treatment for Ingestion

(Swallowing): **Contact medical help immediately; untrained first aid personnel should not attempt to administer first aid.**

Section IX - Precautions for Safe Handling and Use

Steps to be taken in case

material is released or spilled (Dry Stage): **Sweep and dispose of in proper receptacle.**

Steps to be taken in case

material is released or spilled (Wet Stage): **Scoop into proper receptacle and allow to harden.**

Waste Disposal

Method: **Per local, state and federal regulations.**

Precautions To Be Taken

In Handling and Storing: **Store in a cool dry location, out of direct sunlight. Protect from freezing.**

Other Precautions: **This material is an industrial product designed to be used by professionals familiar with the requirements of this MSDS.**

Respiratory Protection:

Respiratory protection is recommended for mixing this product. Respiratory protection is not required for normal use of this product. If material is ground upon or sanded when it is dry, NIOSH/MSHA approved respirators for silica dust should be provided and worn. All workers required to use respiratory protection should be trained in their proper selection, use and care.

Ventilation:

Recommended; local or mechanical when mixing, applying or sanding the product in the dry state.

Protective Gloves:

Recommended; plastic or rubber.

Eye Protection:

Recommended; chemical splash safety goggles.

Other Protective

Equipment: **Recommended; splash bib and protective clothing.**

Section VI - Reactivity Data

Material Safety Data Sheet

CR246 Sto Bonding and Anti-Corrosion Agent

Work and Hygienic

Practices: **Remove and wash contaminated clothing. As with all commercial and industrial products, always wash hands before eating or smoking.**

California Proposition 65: **This product contains crystalline silica (quartz sand), which is considered a carcinogen by the State of California.**

The information and recommendations contained herein are, to the best of Sto Corp.'s knowledge and belief, accurate and reliable as of the date issued. Sto Corp. does not warrant or guarantee their accuracy or reliability, and Sto Corp. shall not be liable for any loss or damage arising out of their use thereof. The information and recommendations are offered for the users' consideration and examination, and it is the users' responsibility to satisfy itself that they are suitable and complete for its particular use.