

Sto Limestone



Affordable Beauty, Durability with Design Flexibility

Sto Corp, the innovative world leader in cladding, coating and restoration systems, combines the classic beauty of stone in a lightweight and easily installed premium architectural wall finish, Sto Limestone. Sto Limestone features the look and feel of natural stone at a fraction of the expense while lending the flexibility of design options to commercial and residential projects.

Various Color Choices

A variety of natural stone colors and 100% acrylic polymer formulation makes Sto Limestone an excellent choice whether the application is new construction or renovation, and over prepared concrete, masonry and plaster substrates and in StoTherm™ Insulated Wall Claddings, including StoTherm™ Classic and StoTherm Classic NExT™.

Contact your local distributor for more information.
Please visit us at www.stocorp.com or call us toll-free at 800-221-2397.

Feature:	Benefit:
Limestone look	Obtain the beauty of natural stone in a durable, acrylic-based finish
Lightweight	Cost savings on materials, application and structural requirements
Integral Color	Lasting uniform color; various color choices
Moisture Resistant	Repels water; resists wind driven rain
Water-based	Safe, non-toxic; cleans up with water
Stolit® Premium Finish	Optilink® advanced polymer technology improves finish performance

Reduced Weight & Cost

When designed as part of a Sto Cladding, a wide variety of costly stone elements like quoins, arches and reliefs can be readily fashioned from lightweight material and finished with Sto Limestone to enhance the beauty of the building design at reduced weight and cost.



Why Use a Sto Limestone Finish?

- Sto Limestone is a custom texture finish that provides the look of natural limestone in an acrylic based finish.
- Allows designers to capitalize on a smooth and natural look without the cost of complex design issues.
- Gives structures a moisture resistant finish by resisting wind driven rain.
- Includes integral color from batch to batch, pail to pail.
- Sto Limestone's texture is achieved by using two Sto 100% acrylic polymer finishes, Stolit® 1.0 and Stolit® Freeform. This is done in two separate applications of finish, so additional cost should be anticipated.
- Sto Limestone can also be achieved in an elastomeric version using Sto Powerflex® Fine and Sto Powerflex Freeform. Use this version when designing with StoPowerwall™ Stucco.
- Use as a full-wall finish or for accent areas to replicate a smooth stone look.



Sto Limestone is available in a variety of standard and custom colors to suit your project needs. Sto's expert color matching capabilities allow us to provide you with an exact match to many of the Limestone colors available around the world.

For Exterior Insulation and Finish Systems (EIFS) select colors with light reflectance value of 20 or greater.

See Tech Hotline Nos. 0694-C, 0893-C and 1202-CF for helpful tips on prevention of color problems.

ATTENTION

Sto products are intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. They should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all, and assumes no, liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, or for other construction activities beyond Sto's control. Improper use of Sto products or use as part of an improperly designed or constructed larger assembly or building may result in serious damage to this product, and to the structure of the building or its components. **STO CORP. DISCLAIMS ALL WARRANTIES EXPRESS OR IMPLIED EXCEPT FOR EXPLICIT LIMITED WRITTEN WARRANTIES ISSUED TO AND ACCEPTED BY BUILDING OWNERS IN ACCORDANCE WITH STO'S WARRANTY PROGRAMS WHICH ARE SUBJECT TO CHANGE FROM TIME TO TIME.** For the fullest, most current information on proper application, clean-up, mixing and other specifications and warranties, cautions and disclaimers, please refer to the Sto Corp. website, www.stocorp.com.

Sto Corp.

3800 Camp Creek Parkway
Building 1400, Suite 120
Atlanta, GA 30331

Tel: 404-346-3666
Toll Free: 1-800-221-2397
Fax: 404-346-3119
www.stocorp.com



S158B 10/07 VEN 6905
Printed in the U.S.A.

sto[®]

