




StoPowerwall™ Stucco Systems with Structalath Twin Trac Reinforcement

Systems Comparison Chart	StoPowerwall NExT with Structalath Twin Trac Chrom-EX™	StoPowerwall with Structalath Twin Trac Chrom-EX™	Generic 3 Coat stucco system
			
Stucco System Warranty	6 to 12 yrs	1 to 7 yrs	None
- Includes StoGuard waterproof air barrier	Yes	No	No
- Includes Structalath Twin Trac	Yes	Yes	No
- Includes StoPowerwall stucco	Yes	Yes	No
- Includes Sto Primers and Finishes	Yes	Yes	No
StoGuard® Waterproof Air Barrier			
- A spray-on building wrap that is waterproof, tear proof, seamless & structural.	Yes	No	No
- A qualified CMCC listed air barrier that can provide energy savings between 10% to 40% when properly installed in tandem with other air barrier components	Yes	No	No
Structalath Twin Trac			
- ICC code recognition	Yes	Yes	Yes
- Up to 30% labor savings on lath installation	Yes	Yes	No
- ¼" flat bottom furring facilitates application for uniform stucco thickness and proper embedding of wire in the stucco	Yes	Yes	No
- Corrosion resistant wire that is 50 times greater than Class 1 Zinc Coated steel as per ASTM-B117 (CHROM EX™ Version only)	Yes	Yes	No
StoPowerwall Stucco			
- ICC code approval	Yes	Yes	Yes
- Stucco mix control in ISO 9001:2000 manufacturing facilities	Yes	Yes	No
- Reduced thickness, which results in reduced dead loads on the structure	Yes	Yes	No