

Stolit® X Finish

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).
Revision Date: 7/29/2025 Version: 2.0

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture

Product Name: Stolit® X Finish: Stolit® X Fine, Stolit® X Medium, Stolit® X Swirl, Stolit® X Freeform

Product Code: 81524, 81525, 81526 , 81527

1.2. Intended Use of the Product

Ready-mixed, acrylic-based, exterior or interior textured wall finish

1.3. Name, Address, and Telephone of the Responsible Party

Company

Sto Corp.

3800 Camp Creek Pkwy

Bldg 1400, Ste 120

Atlanta, GA 30331

404-346-3666

www.stocorp.com

1.4. Emergency Telephone Number

Emergency Number : 800-424-9300 CHEMTREC

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

GHS-US/CA Classification

Not classified

2.2. Label Elements

GHS-US/CA Labeling

No labeling applicable according to 29 CFR 1910.1200 and the Hazardous Products Regulations (HPR) SOR/2015-17.

2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions. This product contains Crystalline Silica dust that is mixed with a liquid to form a paste mixture, and therefore the dust is not likely to be dispersed into the air. If dust is released into the air, repeated exposure to respirable (airborne) crystalline silica dust may cause lung damage in the form of silicosis, lung cancer, or respiratory irritation. This product contains an ingredient that is a potential combustible dust. In sufficient quantities in air with an ignition source this material may present a combustible dust hazard. Take appropriate precautions, avoid sparks and other ignition sources.

2.4. Unknown Acute Toxicity (GHS-US/CA)

No additional information available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

| Name | Synonyms | Product Identifier | % * | GHS Ingredient Classification |
|-----------------------------|---|---------------------|------------|-------------------------------|
| Limestone | Calcium carbonate / Marble / Natural calcium carbonate / Acetate, 4-methyl-2-propyl-2H-tetrahydropyran-4-yl / Limestone (A noncombustible solid characteristic of sedimentary rock. It consists primarily of calcium carbonate.) / Ground limestone / Chalk / Limestone (sedimentary rock) / Calcite / Limestone ground | (CAS-No.) 1317-65-3 | 9.405 – 60 | Not classified |
| Styrene-butadiene copolymer | Benzene, ethenyl-, polymer with 1,3-butadiene / Butadiene-styrene copolymer | (CAS-No.) 9003-55-8 | 6 – 30 | Comb. Dust |

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| | | | | |
|---------------------------------------|--|----------------------|---------|--|
| | / 1,3-Butadiene-styrene copolymer / Butadiene-styrene polymer / 1,3-Butadiene-styrene polymer / Butadiene-styrene resin / Butadiene-styrene rubber / Styrene-1,3-butadiene copolymer / STYRENE/BUTADIENE COPOLYMER / Styrene-butadiene polymer / Styrene/butadiene copolymers / Polymer of styrene and 1,3-butadiene / Styrene-butadiene rubber / 1,3 Butadiene/styrene copolymers / Styrene homopolymer and 1,3-butadiene homopolymer, block copolymer / Polymer of buta-1,3-diene/styrene / Polymer mainly composed of styrene/butadiene | | | |
| Quartz | Quartz (SiO ₂) / Silica, crystalline, quartz / Crystalline silica, quartz / .alpha.-Quartz / Silica, crystalline, .alpha.-quartz / Silica, crystalline-.alpha.quartz / Silica, .alpha.-quartz / Silicon dioxide / Silica, quartz / Silica, crystalline / Quartz (crystalline silica) / Silica dust, crystalline / QUARTZ POWDER / Silica, crystalline (quartz) / Silica dust / Quartz (respirable fraction) / Quartz, silica / Crystalline silica in the form of quartz / QUARTZ | (CAS-No.) 14808-60-7 | 10 – 30 | Carc. 1A, H350 STOT SE 3, H335 STOT RE 1, H372 |
| Silica, amorphous, diatomaceous earth | Diatomaceous earth, ignited / Silica, amorphous and synthetic, diatomaceous earth, calcined / Calcined diatomaceous earth / Silicon dioxide (diatomaceous earth) / Silica, amorphous, soda ash flux-calcined / Flux-calcined diatomaceous earth / Diatomite / Diatomaceous earth, soda ash flux-calcined / Flux calcined diatomaceous earth / Silica, amorphous, silica fume, calcined diatomaceous earth / Diatomaceous earth, natural / Kieselguhr, soda ash, flux calcined / Diatomaceous earth / Silica, amorphous, diatomaceous earth / Diatomaceous earth, calcined / Diatomaceous earth (amorphous) | (CAS-No.) 68855-54-9 | ≤ 10 | STOT RE 1, H372 |
| Acrylic polymers | Acrylic polymer | (CAS-No.) 9065-11-6 | 3 – 7 | Not classified |
| Silica, cristobalite | Cristobalite / Cristobalite (SiO ₂) / Silica, crystalline - cristobalite / Silica, | (CAS-No.) 14464-46-1 | 1 – 7 | Carc. 1A, H350 STOT RE 1, H372 |

Stolit® X Finish

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| | | | | |
|---|---|----------------------|----------------|---|
| | crystalline, cristobalite / Silica-crystalline, cristobalite / Cristobalite (Silica) / Silica, crystalline cristobalite / Silica - crystalline, cristobalite / Silica crystalline cristobalite / Crystalline SiO ₂ , cristobalite / Silica (crystalline, cristobalite) / Silica, crystalline-cristobalite / Silica-crystalline cristobalite / Silica, crystalline (cristobalite) / Silica crystalline / Silica crystalline, cristobalite / Crystalline silica in the form of cristobalite / Silica / Silica, crystalline | | | |
| Titanium dioxide | C.I. 77891 / C.I. Pigment White 6 / Titanium oxide (TiO ₂) / CI 77891 / Titanium(IV) oxide / C.I. Pigment White 7 / Pigment White 6 / Titanium dioxide nanoparticles / Titanium oxide | (CAS-No.) 13463-67-7 | ≤ 5 | Carc. 2, H351 |
| Perlite | Perlite, expanded / Perlit / PERLITE / Expanded perlite | (CAS-No.) 93763-70-3 | ≤ 2 | Not classified |
| Petroleum distillates, hydrotreated light | Odorless light petroleum hydrocarbons / Hydrocarbons, C11-14, n-alkanes, isoalkanes, cyclics, / Distillates (petroleum), hydro-treated light; Kerosine - unspecified [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C9 through C16 and boiling in the range of approximately 150°C to 290°C (302°F to 554°F).] / Distillates (petroleum), hydrotreated light / Kerosene / c13-14 isoparaffin / Destillate (Erdöl), mit Wasserstoff behandelt leichte (C9-14 Aliphaten) / Light Aliphatic Hydrocarbon / Petroleum distillates, hydrotreated light (A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C9-16 and boiling in the range of approximately 150-290°C.) / Kerosene, hydrotreated / Hydrotreated light distillate / Distillates, petroleum, hydrotreated light | (CAS-No.) 64742-47-8 | 0.4925 – 0.985 | Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411 |

Stolit® X Finish

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| | | | | |
|--------------------------------|---|------------------------|------------|---|
| Pyrophyllite | Pyrophyllite (AlH(SiO ₃) ₂) / Potassium aluminosilicate / PYROPHYLLITE / Pyrophyllite clay / Pagodite | (CAS-No.) 12269-78-2 | 0.4 – 0.9 | Eye Irrit. 2A, H319 STOT SE 3, H335 STOT RE 1, H372 |
| Slack wax, petroleum | Slack wax (petroleum), hydrotreated / Slack wax 75 / Slack wax (petroleum); Slack wax [A complex combination of hydrocarbons obtained from a petroleum fraction by solvent crystallization (solvent dewaxing) or as a distillation fraction from a very waxy crude. It consists predominantly of saturated straight and branched chain hydrocarbons having carbon numbers predominantly greater than C20.] / Slack wax, (petroleum) / Wax, slack (petroleum) / Slack wax (petroleum) / Slack wax | (CAS-No.) 64742-61-6 | ≤ 0.6 | Carc. 1B, H350 |
| Sodium carboxymethyl cellulose | CELLULOSE GUM / Sodium salt of carboxymethyl ether of cellulose / Carmellose sodium / Cellulose gum / Carboxymethylcellulose sodium / Carboxyl methyl cellulose / Carboxymethyl cellulose sodium salt / Sodium salt of polyanionic polysaccharide based on glucose / Sodium poly-1,4-β-D-O-carboxymethyl-D-pyranosyl-D-glucopyranose / Sodium salt of cellulose carboxymethyl ether / Sodium carboxymethyl starch / Sodium carboxy methyl cellulose / Carboxymethylcellulose / Cellulose carboxy methyl ether, sodium salt / Sodium carboxymethylcellulose / Sodium salt of carboxymethylcellulose / CMC sodium salt / CM-Cellulose sodium salt / Cellulose, carboxymethyl ether, sodium salt / Cellulose glycolic acid, sodium salt / Cellulose carboxymethyl ether, sodium salt / Carboxymethylcellulose, sodium salt / Carboxymethylcellulose sodium salt / Carboxymethyl cellulose, sodium salt | (CAS-No.) 9004-32-4 | ≤ 0.439 | Aquatic Acute 3, H402 Comb. Dust |
| Mica | C.I. Pigment White 20 / Pigment White 20 / MICA / Mica-group minerals / C.I. 77019 / Silicates, mica / Mica group minerals / Mica dust | (CAS-No.) 12001-26-2 | 0.05 – 0.4 | Not classified |
| Kaolin | KAOLIN | (CAS-No.) 1332-58-7 | 0.02 – 0.2 | Not classified |
| Emulsifier | - | (CAS-No.) TRADE SECRET | < 0.05 | Not classified |

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| | | | | |
|---|--|----------------------|----------------|--|
| 2-Amino-2-methyl-1-propanol | 2-Amino-2-methylpropan-1-ol / Isobutanol-2-amine / Isobutanolamine / Propan-1-ol, 2-amino-2-methyl- / 1-Propanol, 2-amino-2-methyl- / 2-Amino-2-methylpropanol / AMINOMETHYL PROPANOL / Aminomethyl propanol / AMP / Aminomethylpropanol | (CAS-No.) 124-68-5 | ≤ 0.05 | Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Aquatic Chronic 3, H412 |
| Ammonium hydroxide | Ammonia, aqueous solution / Ammonium hydroxide ((NH ₄)(OH)) / Ammonia aqueous / Ammonia solution / AMMONIUM HYDROXIDE / Ammonia, aqueous / Ammonia solutions / Ammonia ...% / Ammonia water / Ammonia | (CAS-No.) 1336-21-6 | ≤ 0.03 | Met. Corr. 1, H290 Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 1, H400 |
| Benzophenone | Benzoylbenzene / Diphenyl ketone / Methanone, diphenyl- / BENZOPHENONE | (CAS-No.) 119-61-9 | 0.01 – 0.03 | Carc. 2, H351 STOT RE 2, H373 Aquatic Acute 2, H401 Aquatic Chronic 3, H412 |
| 1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)- | Propane-1,3-diol, 2-ethyl-2-(hydroxymethyl)- / Propylidynetrimethanol / TMP / 1,1,1-Tri(hydroxymethyl)propane / 1,1,1-Trimethylolpropane / Trimethylolpropane / 1,1,1-Tris(hydroxymethyl)propane / 2-Ethyl-2-(hydroxymethyl)-1,3-propanediol / 2,2-Bis(hydroxymethyl)-1-butanol / 2,2-Bis(hydroxymethyl)butan-1-ol / 2,2-Dihydroxymethylbutanol / TRIMETHYLOLPROPANE | (CAS-No.) 77-99-6 | 0.001 – 0.0225 | Not classified |
| 1,2-Benzisothiazol-3(2H)-one | 1,2-Benzisothiazolin-3-one / Benzisothiazolinone / 1,2-Benzisothiazolone / 1,2-Benzisothiazol-3-one / Benzisothiazolin-3-one, 1,2- / BENZISOTHIAZOLINONE / benzisothiazolinone | (CAS-No.) 2634-33-5 | ≤ 0.021 | Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Comb. Dust |
| Naphtha, petroleum, hydrotreated heavy | Naphtha, (petroleum), hydrotreated heavy / Naphtha, petroleum, hydrotreated heavy (A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C6-13 and boiling in the range of approximately 65-230°C.) / Synthetic isoparaffin, C6-13 / Naphtha (petroleum), hydrotreated heavy - low boiling point hydrogen treated naphtha / C10-12 ALKANE/CYCLOALKANE / | (CAS-No.) 64742-48-9 | 0.0075 – 0.015 | Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304 |

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| | | | | |
|--------------------------------|--|---------------------|----------|---|
| | Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha / Naphtha, petroleum, hydrotreated, heavy / Ligroine (petroleum), hydrotreated heavy / Hydrocarbons, C9-11, n-alkanes, isoalkanes, cyclics, < 2% aromatics / Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C6 through C13 and boiling in the range of approximately 65°C to 230°C (149°F to 446°F).] / Aliphatic oil / c9-11 alkane/cycloalkane / Naphtha (petroleum), hydrotreated heavy / White spirit type 3 / Isopar 350 / Naphtha (petroleum), hydrotreated heavy - low boiling point thermally cracked naphtha / Hydrotreated heavy naphtha (petroleum) / Hydrotreated heavy naphtha | | | |
| 3(2H)-Isothiazolone, 2-methyl- | 2-Methyl-3-isothiazolone / 3-Isothiazolone, 2-methyl- / 2-Methyl-2H-isothiazol-3-one / 2-Methyl-4-isothiazolin-3-one / 2-Methyl-4-isothiazolone-3-one / Methylisothiazolinone / Methylisothiazolone / Methyl-4-isothiazolin-3-one, 2- / METHYLISOTHIAZOLINONE / MIT / 2-Methyl-2,3-dihydroisothiazol-3-one / 2-Methylisothiazol-3(2H)-one / 3(2H)-Isothiazolone-3-one, 2-methyl- / 2-Methylisothiazolin-3(2H)-one / N-Methyl-isothiazolone / methylisothiazolinone | (CAS-No.) 2682-20-4 | ≤ 0.0105 | Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 2 (Inhalation:dust,mist), H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 STOT SE 3, H335 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 |
| Sodium chloride | Salt / SEA SALT / Sodium salt of hydrochloric acid / SODIUM CHLORIDE / Sodium chloride (NaCl) / Sea salt | (CAS-No.) 7647-14-5 | ≤ 0.01 | Not classified |
| Residual Monomers | - | | < 0.0075 | STOT SE 3, H335 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Acute 3, H402 Aquatic Chronic 3, H412 |
| Ethanedial | Glyoxal / GLYOXAL / Glyoxal ...% / Ethane-1,2-dione / Ethandial ...% / Oxalaldehyde / 1,2-Ethanedione | (CAS-No.) 107-22-2 | ≤ 0.005 | Acute Tox. 3 (Oral), H301 Acute Tox. 4 (Inhalation:dust,mist), H332 |

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| | | | | |
|---|---|----------------------|----------|---|
| | | | | Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317 Muta. 2, H341 STOT SE 3, H335 |
| Propanol, 2-(methylamino)- 2-methyl- | 2-Methyl-2-(methylamino)propan-1-ol / 1-Propanol, 2-methyl-2-(methylamino)- / 2-Methyl-2-(methylamino)-1-propanol / 2-methyl-2-methylamino-1-propanol | (CAS-No.) 27646-80-6 | ≤ 0.005 | Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 |
| 2,2,4-Trimethyl-1,3-pentanediol diisobutyrate | TXIB / Texanolisobutyrate / 2,2,4-Trimethylpentanediol diisobutyrate / Trimethyl pentanyl diisobutyrate / 2,2,4-Trimethylpentane-1,3-diyl diisobutyrate / TRIMETHYL PENTANYL DIISOBUTYRATE / Propanoic acid, 2-methyl-, 1,1'-[2,2-dimethyl-1-(1-methylethyl)-1,3-propanediyl] ester / Propanoic acid, 2-methyl-, 2,2-dimethyl-1-(1-methylethyl)-1,3-propanediyl ester / 1-Isopropyl-2,2-dimethyltrimethylene diisobutyrate / Isobutyric acid, 1-isopropyl-2,2-dimethyltrimethylene ester / Diisobutyrate, 2,2,4-trimethyl-1,3-pentanedyl | (CAS-No.) 6846-50-0 | ≤ 0.004 | Repr. 2, H361 Aquatic Acute 2, H401 Aquatic Chronic 2, H411 |
| 3(2H)-Isothiazolone, 5-chloro-2-methyl- | 5-Chloro-2-methyl-3-isothiazolone / 5-Chloro-2-methyl-2H-isothiazol-3-one / 5-Chloro-2-methyl-4-isothiazolin-3-one / Isothiazol(2H)-3-one, 5-chloro-2-methyl- / 4-Isothiazolin-3-one, 5-chloro-2-methyl- / Methylchloroisothiazolinone / METHYLCHLOROISOTHIAZOLINONE / 5-Chloro-2-methyl-3(2H)-isothiazolone / 2-Methyl-5-chloroisothiazolin-3-one / 5-Chloro-2-methyl-isothiazolone-3(2H)-one / 2-Methyl-5-chloro-2H-isothiazol-3-one / 3(2H)-Isothiazolin-3-one, 5-chloro-2-methyl- / CIT / 5-Chloro-2-methyl-isothiazolin-3(2H)-one / 5-Chloro-2-methyl-4-thiazoline-3-ketone / 5-Chloro-2-methylisothiazol-3(2H)-one / 2H-Isothiazol-3-one, 5-chloro-2-methyl- / 5-Chloro-2-methylisothiazolone / methylchloroisothiazolinone | (CAS-No.) 26172-55-4 | ≤ 0.0021 | Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 |

Full text of H-statements: see section 16

Stolit® X Finish

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

* The actual concentration of ingredient(s) is withheld as a trade secret in accordance with the Hazardous Products Regulations (HPR) SOR/2015-17 and 29 CFR 1910.1200. Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%). Full text of H-statements: see section 16.

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

Skin Contact: Remove contaminated clothing. Wash affected area with soap and water for at least 5 minutes. Obtain medical attention if irritation develops or persists.

Eye Contact: Rinse cautiously with water for at least 5 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.

Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

General: Not expected to present a significant hazard under anticipated conditions of normal use. Contact with dusts from cutting/sanding/lathing/milling/grinding operation may produce the following symptoms. May cause damage to organs (lungs, respiratory system) through prolonged or repeated exposure (Inhalation). May cause cancer by inhalation.

Inhalation: Prolonged exposure may cause irritation. This product contains Crystalline Silica dust that is mixed with a liquid to form a paste mixture, and therefore the dust is not likely to be dispersed into the air. If dust is released into the air, repeated exposure to respirable (airborne) crystalline silica dust may cause lung damage in the form of silicosis, lung cancer, or respiratory irritation.

Skin Contact: Prolonged exposure may cause skin irritation.

Eye Contact: May cause slight irritation to eyes.

Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: This product contains Crystalline Silica dust that is mixed with a liquid to form a paste mixture, and therefore the dust is not likely to be dispersed into the air. If dust is released into the air, repeated exposure to respirable (airborne) crystalline silica dust may cause lung damage in the form of silicosis, lung cancer, or respiratory irritation. May cause cancer by inhalation. May produce an allergic reaction.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Water spray, fog, carbon dioxide (CO₂), alcohol-resistant foam, or dry chemical.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Product is not explosive. Contains substances that are combustible dusts. If dried and allowed to accumulate, may form combustible dust concentrations in air that could ignite and cause an explosion. Take appropriate precautions.

Reactivity: Hazardous reactions will not occur under normal conditions.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides, Nitrogen oxides. Silica compounds. Calcium oxides. Titanium oxides. Hydrocarbons.

5.4. Reference to Other Sections

Refer to Section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid prolonged contact with eyes, skin and clothing. Avoid breathing (vapor, mist, spray). The following applies to the product if it is cut, sanded or altered in such a way that excessive and/or significant particulates and/or dusts may be generated: Avoid breathing dust.

Stolit® X Finish

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Absorb and/or contain spill with inert material. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: This product contains Crystalline Silica dust that is mixed with a liquid to form a paste mixture, and therefore the dust is not likely to be dispersed into the air. If dust is released into the air, repeated exposure to respirable (airborne) crystalline silica dust may cause lung damage in the form of silicosis, lung cancer, or respiratory irritation.

Precautions for Safe Handling: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid prolonged contact with eyes, skin and clothing. Avoid breathing vapors, mist, spray.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Materials: Strong acids, strong bases, strong oxidizers.

7.3. Specific End Use(s)

Ready-mixed, acrylic-based, exterior or interior textured wall finish

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

| Silica, amorphous, diatomaceous earth (68855-54-9) | | |
|--|-------------------------|--|
| Yukon | OEL TWA | 300 particle/mL (as measured by Konimeter instrumentation (Silica) 20 mppcf (as measured by Impinger instrumentation (Silica) 1.5 mg/m ³ (respirable mass (Silica) |
| Silica, cristobalite (14464-46-1) | | |
| USA ACGIH | ACGIH OEL TWA | 0.025 mg/m ³ (respirable particulate matter) |
| USA ACGIH | ACGIH chemical category | Suspected Human Carcinogen |
| USA OSHA | OSHA PEL (TWA) [1] | 50 µg/m ³ (Respirable crystalline silica) |
| USA OSHA | OSHA PEL (TWA) [2] | (1/2)(250)/(%SiO ₂ +5) mppcf (respirable fraction) (1/2)(10)/(%SiO ₂ +2) mg/m ³ (respirable fraction) (For any operations or sectors for which the respirable crystalline silica standard, 1910.1053, is stayed or otherwise not in effect, See 29 CFR 1910.1000 TABLE Z-3) |
| USA NIOSH | NIOSH REL (TWA) | 0.05 mg/m ³ (respirable dust) |

Stolit® X Finish

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| | | |
|------------------------------------|-------------------------|--|
| USA IDLH | IDLH | 25 mg/m ³ (respirable dust) |
| Alberta | OEL TWA | 0.025 mg/m ³ (respirable particulate) |
| British Columbia | OEL TWA | 0.025 mg/m ³ (respirable) |
| Manitoba | OEL TWA | 0.025 mg/m ³ (respirable particulate matter) |
| New Brunswick | OEL TWA | 0.05 mg/m ³ (respirable fraction) |
| Newfoundland & Labrador | OEL TWA | 0.025 mg/m ³ (respirable particulate matter) |
| Nova Scotia | OEL TWA | 0.025 mg/m ³ (respirable particulate matter) |
| Nunavut | OEL TWA | 0.05 mg/m ³ (Trydimite removed-respirable fraction (Silica - crystalline)) |
| Northwest Territories | OEL TWA | 0.05 mg/m ³ (Trydimite removed-respirable fraction (Silica - crystalline)) |
| Ontario | OEL TWA | 0.05 mg/m ³ (designated substances regulation-respirable fraction (Silica, crystalline)) |
| Prince Edward Island | OEL TWA | 0.025 mg/m ³ (respirable particulate matter) |
| Québec | VEMP (OEL TWA) | 0.05 mg/m ³ (respirable dust) |
| Saskatchewan | OEL TWA | 0.05 mg/m ³ (Trydimite removed-respirable fraction (Silica - crystalline (Trydimite removed))) |
| Yukon | OEL TWA | 150 particle/mL (Silica) |
| Residual Monomers | | |
| | Internal OEL Value(s) | Internal TWA: 4 ppm (Skin); Internal STEL: 10 ppm (Skin) |
| USA ACGIH | ACGIH OEL TWA [ppm] | 20 ppm |
| Benzophenone (119-61-9) | | |
| USA AIHA | WEEL TWA | 0.5 mg/m ³ |
| Limestone (1317-65-3) | | |
| USA OSHA | OSHA PEL (TWA) [1] | 15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction) |
| USA NIOSH | NIOSH REL (TWA) | 10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust) |
| Alberta | OEL TWA | 10 mg/m ³ |
| British Columbia | OEL STEL | 20 mg/m ³ (total) |
| British Columbia | OEL TWA | 10 mg/m ³ (total dust) 3 mg/m ³ (respirable fraction) |
| New Brunswick | OEL TWA | 10 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica) |
| Nunavut | OEL STEL | 20 mg/m ³ |
| Nunavut | OEL TWA | 10 mg/m ³ |
| Northwest Territories | OEL STEL | 20 mg/m ³ |
| Northwest Territories | OEL TWA | 10 mg/m ³ |
| Québec | VEMP (OEL TWA) | 10 mg/m ³ (Limestone, containing no Asbestos and <1% Crystalline silica-total dust) |
| Saskatchewan | OEL STEL | 20 mg/m ³ |
| Saskatchewan | OEL TWA | 10 mg/m ³ |
| Yukon | OEL STEL | 20 mg/m ³ |
| Yukon | OEL TWA | 30 mppcf 10 mg/m ³ |
| Quartz (14808-60-7) | | |
| USA ACGIH | ACGIH OEL TWA | 0.025 mg/m ³ (respirable particulate matter) |
| USA ACGIH | ACGIH chemical category | A2 - Suspected Human Carcinogen |
| USA OSHA | OSHA PEL (TWA) [1] | 50 µg/m ³ (Respirable crystalline silica) |
| USA OSHA | OSHA PEL (TWA) [2] | (250)/(%SiO ₂ +5) mppcf TWA (respirable fraction) (10)/(%SiO ₂ +2) mg/m ³ TWA (respirable fraction) (For any operations or sectors for which the respirable |

Stolit® X Finish



Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| | | |
|--------------------------------------|-------------------------|---|
| | | crystalline silica standard, 1910.1053, is stayed or otherwise not in effect, See 20 CFR 1910.1000 TABLE Z-3) |
| USA NIOSH | NIOSH REL (TWA) | 0.05 mg/m ³ (respirable dust) |
| USA IDLH | IDLH | 50 mg/m ³ (respirable dust) |
| Alberta | OEL TWA | 0.025 mg/m ³ (respirable particulate) |
| British Columbia | OEL TWA | 0.025 mg/m ³ (respirable) |
| Manitoba | OEL TWA | 0.025 mg/m ³ (respirable particulate matter) |
| New Brunswick | OEL TWA | 0.1 mg/m ³ (respirable fraction) |
| Newfoundland & Labrador | OEL TWA | 0.025 mg/m ³ (respirable particulate matter) |
| Nova Scotia | OEL TWA | 0.025 mg/m ³ (respirable particulate matter) |
| Nunavut | OEL TWA | 0.05 mg/m ³ (Trydimite removed-respirable fraction (Silica - crystalline) |
| Northwest Territories | OEL TWA | 0.05 mg/m ³ (Trydimite removed-respirable fraction (Silica - crystalline) |
| Ontario | OEL TWA | 0.1 mg/m ³ (designated substances regulation-respirable fraction (Silica, crystalline) |
| Prince Edward Island | OEL TWA | 0.025 mg/m ³ (respirable particulate matter) |
| Québec | VEMP (OEL TWA) | 0.1 mg/m ³ (respirable dust) |
| Saskatchewan | OEL TWA | 0.05 mg/m ³ (Trydimite removed-respirable fraction (Silica - crystalline (Trydimite removed)) |
| Yukon | OEL TWA | 300 particle/mL (Silica - Quartz, crystalline) |
| Ethanedial (107-22-2) | | |
| USA ACGIH | ACGIH OEL TWA | 0.1 mg/m ³ (inhalable fraction and vapor) |
| USA ACGIH | ACGIH chemical category | Not Classifiable as a Human Carcinogen,dermal sensitizer |
| USA AIHA | WEEL TWA | 0.1 mg/m ³ (aerosol) |
| USA AIHA | AIHA chemical category | Skin sensitizer |
| Alberta | OEL TWA | 0.1 mg/m ³ |
| British Columbia | OEL TWA | 0.1 mg/m ³ (inhalable; inhalable aerosol and vapour) |
| Manitoba | OEL TWA | 0.1 mg/m ³ (inhalable fraction and vapor) |
| Newfoundland & Labrador | OEL TWA | 0.1 mg/m ³ (inhalable fraction and vapor) |
| Nova Scotia | OEL TWA | 0.1 mg/m ³ (inhalable fraction and vapor) |
| Nunavut | OEL STEL | 0.3 mg/m ³ (inhalable fraction and vapour) |
| Nunavut | OEL TWA | 0.1 mg/m ³ (inhalable fraction and vapour) |
| Northwest Territories | OEL STEL | 0.3 mg/m ³ (inhalable fraction and vapour) |
| Northwest Territories | OEL TWA | 0.1 mg/m ³ (inhalable fraction and vapour) |
| Ontario | OEL TWA | 0.1 mg/m ³ (inhalable fraction and vapor) |
| Prince Edward Island | OEL TWA | 0.1 mg/m ³ (inhalable fraction and vapor) |
| Saskatchewan | OEL STEL | 0.3 mg/m ³ (inhalable fraction and vapour) |
| Saskatchewan | OEL TWA | 0.1 mg/m ³ (inhalable fraction and vapour) |
| Titanium dioxide (13463-67-7) | | |
| USA ACGIH | ACGIH OEL TWA | 10 mg/m ³ |
| USA ACGIH | ACGIH chemical category | Not Classifiable as a Human Carcinogen |
| USA OSHA | OSHA PEL (TWA) [1] | 15 mg/m ³ (total dust) |
| USA NIOSH | NIOSH REL (TWA) | 2.4 mg/m ³ (CIB 63-fine) 0.3 mg/m ³ (CIB 63-ultrafine, including engineered nanoscale) |
| USA IDLH | IDLH | 5000 mg/m ³ |
| Alberta | OEL TWA | 10 mg/m ³ |
| British Columbia | OEL TWA | 10 mg/m ³ (total dust) 3 mg/m ³ (respirable fraction) |
| Manitoba | OEL TWA | 10 mg/m ³ |
| New Brunswick | OEL TWA | 10 mg/m ³ |

Stolit® X Finish

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| | | |
|------------------------------------|--------------------|---|
| Newfoundland & Labrador | OEL TWA | 10 mg/m ³ |
| Nova Scotia | OEL TWA | 10 mg/m ³ |
| Nunavut | OEL STEL | 20 mg/m ³ |
| Nunavut | OEL TWA | 10 mg/m ³ |
| Northwest Territories | OEL STEL | 20 mg/m ³ |
| Northwest Territories | OEL TWA | 10 mg/m ³ |
| Ontario | OEL TWA | 10 mg/m ³ |
| Prince Edward Island | OEL TWA | 10 mg/m ³ |
| Québec | VEMP (OEL TWA) | 10 mg/m ³ (containing no Asbestos and <1% Crystalline silica-total dust) |
| Saskatchewan | OEL STEL | 20 mg/m ³ |
| Saskatchewan | OEL TWA | 10 mg/m ³ |
| Yukon | OEL STEL | 20 mg/m ³ |
| Yukon | OEL TWA | 30 mppcf 10 mg/m ³ |
| Perlite (93763-70-3) | | |
| USA OSHA | OSHA PEL (TWA) [1] | 15 mg/m ³ (General Industry - total dust) |
| USA NIOSH | NIOSH REL (TWA) | 10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust) |
| British Columbia | OEL TWA | 10 mg/m ³ (total dust) 3 mg/m ³ (respirable fraction) |
| New Brunswick | OEL TWA | 10 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica) |
| Nunavut | OEL STEL | 20 mg/m ³ |
| Nunavut | OEL TWA | 10 mg/m ³ |
| Northwest Territories | OEL STEL | 20 mg/m ³ |
| Northwest Territories | OEL TWA | 10 mg/m ³ |
| Saskatchewan | OEL STEL | 20 mg/m ³ |
| Saskatchewan | OEL TWA | 10 mg/m ³ |
| Yukon | OEL TWA | 30 mppcf |
| Mica (12001-26-2) | | |
| USA ACGIH | ACGIH OEL TWA | 0.1 mg/m ³ (respirable particulate matter) |
| USA OSHA | OSHA PEL (TWA) [2] | 20 mppcf (<1% Crystalline silica) (See 20 CFR 1910.1000 TABLE Z-3) |
| USA NIOSH | NIOSH REL (TWA) | 3 mg/m ³ (containing <1% Quartz-respirable dust) |
| USA IDLH | IDLH | 1500 mg/m ³ (containing <1% quartz) |
| Alberta | OEL TWA | 3 mg/m ³ (respirable) |
| British Columbia | OEL TWA | 3 mg/m ³ (respirable) |
| Manitoba | OEL TWA | 0.1 mg/m ³ (respirable particulate matter) |
| New Brunswick | OEL TWA | 3 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica, respirable fraction) |
| Newfoundland & Labrador | OEL TWA | 0.1 mg/m ³ (respirable particulate matter) |
| Nova Scotia | OEL TWA | 0.1 mg/m ³ (respirable particulate matter) |
| Nunavut | OEL STEL | 6 mg/m ³ (respirable fraction) |
| Nunavut | OEL TWA | 3 mg/m ³ (respirable fraction) |
| Northwest Territories | OEL STEL | 6 mg/m ³ (respirable fraction) |
| Northwest Territories | OEL TWA | 3 mg/m ³ (respirable fraction) |
| Ontario | OEL TWA | 3 mg/m ³ (respirable particulate matter) |
| Prince Edward Island | OEL TWA | 0.1 mg/m ³ (respirable particulate matter) |
| Québec | VEMP (OEL TWA) | 3 mg/m ³ (containing no Asbestos and <1% Crystalline silica-respirable dust) |
| Saskatchewan | OEL STEL | 6 mg/m ³ (respirable fraction) |

Stolit® X Finish

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| | | |
|---------------------------|-------------------------|---|
| Saskatchewan | OEL TWA | 3 mg/m ³ (respirable fraction) |
| Yukon | OEL TWA | 20 mppcf |
| Kaolin (1332-58-7) | | |
| USA ACGIH | ACGIH OEL TWA | 2 mg/m ³ (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter) |
| USA ACGIH | ACGIH chemical category | Not Classifiable as a Human Carcinogen |
| USA OSHA | OSHA PEL (TWA) [1] | 15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction) |
| USA NIOSH | NIOSH REL (TWA) | 10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust) |
| Alberta | OEL TWA | 2 mg/m ³ (respirable) |
| British Columbia | OEL TWA | 2 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica-respirable particulate) |
| Manitoba | OEL TWA | 2 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica, respirable particulate matter-particulate matter, respirable particulate matter) |
| New Brunswick | OEL TWA | 2 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica, respirable fraction) |
| Newfoundland & Labrador | OEL TWA | 2 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica, respirable particulate matter-particulate matter, respirable particulate matter) |
| Nova Scotia | OEL TWA | 2 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica, respirable particulate matter-particulate matter, respirable particulate matter) |
| Nunavut | OEL STEL | 4 mg/m ³ (respirable fraction) |
| Nunavut | OEL TWA | 2 mg/m ³ (respirable fraction) |
| Northwest Territories | OEL STEL | 4 mg/m ³ (respirable fraction) |
| Northwest Territories | OEL TWA | 2 mg/m ³ (respirable fraction) |
| Ontario | OEL TWA | 2 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica-respirable particulate matter) |
| Prince Edward Island | OEL TWA | 2 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica, respirable particulate matter-particulate matter, respirable particulate matter) |
| Québec | VEMP (OEL TWA) | 2 mg/m ³ (containing no Asbestos and <1% Crystalline silica-respirable dust) |
| Saskatchewan | OEL STEL | 4 mg/m ³ (respirable fraction) |
| Saskatchewan | OEL TWA | 2 mg/m ³ (respirable fraction) |
| Yukon | OEL STEL | 20 mg/m ³ |
| Yukon | OEL TWA | 30 mppcf 10 mg/m ³ |

8.2. Exposure Controls

Appropriate Engineering Controls: Suitable eye/body wash equipment should be available in the vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

Personal Protective Equipment: Gloves. Protective clothing. Protective goggles.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear protective gloves.

Eye and Face Protection: Chemical goggles or safety glasses.

Skin and Body Protection: Wear suitable protective clothing.

Stolit® X Finish

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

| | |
|--|---------------------|
| Physical State | : Liquid |
| Appearance | : Wet |
| Odor | : Slight |
| Odor Threshold | : No data available |
| pH | : 7.5 – 10 |
| Evaporation Rate | : No data available |
| Melting Point | : 0 °C (32 °F) |
| Freezing Point | : 0 °C (32 °F) |
| Boiling Point | : No data available |
| Flash Point | : No data available |
| Auto-ignition Temperature | : No data available |
| Decomposition Temperature | : No data available |
| Flammability | : Not applicable |
| Lower Flammable Limit | : No data available |
| Upper Flammable Limit | : No data available |
| Vapor Pressure | : No data available |
| Relative Vapor Density at 20°C | : No data available |
| Relative Density | : No data available |
| Specific Gravity | : > 1 (water = 1) |
| Solubility | : No data available |
| Partition Coefficient: N-Octanol/Water | : No data available |
| Viscosity | : No data available |

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity:

Hazardous reactions will not occur under normal conditions.

10.2. Chemical Stability:

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of Hazardous Reactions:

Hazardous polymerization will not occur. Product is not a dust as supplied; however, product dusts may be combustible.

10.4. Conditions to Avoid:

Direct sunlight, extremely high or low temperatures, and incompatible materials.

10.5. Incompatible Materials:

Strong acids, strong bases, strong oxidizers.

10.6. Hazardous Decomposition Products:

Thermal decomposition may produce: Carbon oxides, Nitrogen oxides. Oxides of titanium. Silicon oxides. Oxides of calcium. Hydrocarbons.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects - Product

Acute Toxicity (Oral): Not classified

Acute Toxicity (Dermal): Not classified

Acute Toxicity (Inhalation): Not classified

LD50 and LC50 Data:

No additional information available

Skin Corrosion/Irritation: Not classified

pH: 7.5 – 10

Eye Damage/Irritation: Not classified

pH: 7.5 – 10

Stolit® X Finish

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Carcinogenicity: Not classified.

Specific Target Organ Toxicity (Repeated Exposure): Not classified.

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified.

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Prolonged exposure may cause irritation. This product contains Crystalline Silica dust that is mixed with a liquid to form a paste mixture, and therefore the dust is not likely to be dispersed into the air. If dust is released into the air, repeated exposure to respirable (airborne) crystalline silica dust may cause lung damage in the form of silicosis, lung cancer, or respiratory irritation.

Symptoms/Injuries After Skin Contact: Prolonged exposure may cause skin irritation.

Symptoms/Injuries After Eye Contact: May cause slight irritation to eyes.

Symptoms/Injuries After Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: This product contains Crystalline Silica dust that is mixed with a liquid to form a paste mixture, and therefore the dust is not likely to be dispersed into the air. If dust is released into the air, repeated exposure to respirable (airborne) crystalline silica dust may cause lung damage in the form of silicosis, lung cancer, or respiratory irritation, May cause cancer by inhalation, May produce an allergic reaction

11.2. Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

| | |
|--|---|
| 1,2-Benzisothiazol-3(2H)-one (2634-33-5) | |
| LD50 Oral Rat | 1020 mg/kg |
| LD50 Dermal Rat | > 2000 mg/kg |
| 3(2H)-Isothiazolone, 2-methyl- (2682-20-4) | |
| LD50 Oral Rat | 120 mg/kg |
| LD50 Dermal Rabbit | 242 mg/kg |
| LC50 Inhalation Rat | 0.11 mg/l/4h |
| 3(2H)-Isothiazolone, 5-chloro-2-methyl- (26172-55-4) | |
| LD50 Oral Rat | 481 mg/kg |
| LC50 Inhalation Rat | 1.23 mg/l/4h |
| 2,2,4-Trimethyl-1,3-pentanediol diisobutyrate (6846-50-0) | |
| LD50 Oral Rat | > 3200 mg/kg |
| LD50 Dermal Rabbit | > 2000 mg/kg |
| LC50 Inhalation Rat | > 5.3 mg/l (Exposure time: 6 h) |
| Silica, amorphous, diatomaceous earth (68855-54-9) | |
| LD50 Oral Rat | > 2000 mg/kg |
| LC50 Inhalation Rat | > 2.6 mg/l/4h (No deaths) |
| LC50 Inhalation Rat | > 2.6 mg/l/4h |
| Ammonium hydroxide (1336-21-6) | |
| LD50 Oral Rat | 350 mg/kg |
| Benzophenone (119-61-9) | |
| LD50 Oral Rat | > 10 g/kg |
| LD50 Dermal Rabbit | 3535 mg/kg |
| Quartz (14808-60-7) | |
| LD50 Oral Rat | > 5000 mg/kg |
| LD50 Dermal Rat | > 5000 mg/kg |
| Sodium carboxymethyl cellulose (9004-32-4) | |
| LD50 Oral Rat | 27000 mg/kg |
| LD50 Dermal Rabbit | > 2000 mg/kg |
| LC50 Inhalation Rat | > 5800 mg/m ³ (Exposure time: 4 h) |
| LC50 Inhalation Rat | > 5.8 mg/l/4h |

Stolit® X Finish

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| | |
|---|---|
| Sodium chloride (7647-14-5) | |
| LD50 Oral Rat | 3550 mg/kg (Species: Wistar) |
| LD50 Dermal Rabbit | > 10000 mg/kg (Species: New Zealand White) |
| LC50 Inhalation Rat | > 42 mg/l (Exposure time: 1 h) |
| Ethanedial (107-22-2) | |
| LD50 Oral Rat | 200 mg/kg |
| LD50 Dermal Rabbit | 12700 mg/kg |
| LC50 Inhalation Rat | 2.44 mg/l/4h |
| LC50 Inhalation Rat | 2.44 mg/l/4h |
| 1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)- (77-99-6) | |
| LD50 Oral Rat | 14100 mg/kg |
| LD50 Dermal Rabbit | > 10000 mg/kg |
| Titanium dioxide (13463-67-7) | |
| LD50 Oral Rat | > 10000 mg/kg |
| LC50 Inhalation Rat | 5.09 mg/l/4h |
| Petroleum distillates, hydrotreated light (64742-47-8) | |
| LD50 Oral Rat | > 5000 mg/kg |
| LD50 Dermal Rabbit | > 2000 mg/kg |
| LC50 Inhalation Rat | > 5.3 mg/l/4h |
| Naphtha, petroleum, hydrotreated heavy (64742-48-9) | |
| LD50 Oral Rat | > 6000 mg/kg |
| LD50 Dermal Rabbit | > 5000 mg/kg |
| LC50 Inhalation Rat | > 8500 mg/m ³ (Exposure time: 4 h) |
| Perlite (93763-70-3) | |
| LD50 Oral Rat | 12960 mg/kg (Mouse) |
| 2-Amino-2-methyl-1-propanol (124-68-5) | |
| LD50 Oral Rat | 2900 mg/kg |
| LD50 Dermal Rabbit | > 2000 mg/kg |
| Propanol, 2-(methylamino)-2-methyl- (27646-80-6) | |
| ATE US/CA (oral) | 500.00 mg/kg body weight |
| Kaolin (1332-58-7) | |
| LD50 Oral Rat | > 5000 mg/kg |
| LD50 Dermal Rat | > 5000 mg/kg |
| LD50 Dermal Rabbit | > 5000 mg/kg |
| Styrene-butadiene copolymer (9003-55-8) | |
| IARC Group | 3 |
| Silica, amorphous, diatomaceous earth (68855-54-9) | |
| IARC Group | 3 |
| Silica, cristobalite (14464-46-1) | |
| IARC Group | 1 |
| National Toxicology Program (NTP) Status | Known Human Carcinogens. |
| OSHA Hazard Communication Carcinogen List | In OSHA Hazard Communication Carcinogen list. |
| Benzophenone (119-61-9) | |
| IARC Group | 2B |
| National Toxicology Program (NTP) Status | Evidence of Carcinogenicity. |
| OSHA Hazard Communication Carcinogen List | In OSHA Hazard Communication Carcinogen list. |
| Quartz (14808-60-7) | |
| IARC Group | 1 |
| National Toxicology Program (NTP) Status | Known Human Carcinogens. |
| OSHA Hazard Communication Carcinogen List | In OSHA Hazard Communication Carcinogen list. |

| | |
|-------------------------------|----|
| Titanium dioxide (13463-67-7) | |
| IARC Group | 2B |

SECTION 12: ECOLOGICAL INFORMATION**12.1. Toxicity**

Ecology - General: Not classified.

| | |
|--|---|
| 1,2-Benzisothiazol-3(2H)-one (2634-33-5) | |
| EC50 - Crustacea [1] | 0.99 mg/l |
| 3(2H)-Isothiazolone, 5-chloro-2-methyl- (26172-55-4) | |
| LC50 Fish 1 | 1.6 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static]) |
| EC50 - Crustacea [1] | 4.71 mg/l (Exposure time: 48 h - Species: Daphnia magna) |
| EC50 - Crustacea [2] | 0.12 (0.12 – 0.3) mg/l (Exposure time: 48 h - Species: Daphnia magna [Flow through]) |
| 2,2,4-Trimethyl-1,3-pentanediol diisobutyrate (6846-50-0) | |
| LC50 Fish 1 | 6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static]) |
| EC50 - Crustacea [1] | > 1.46 mg/l (Exposure time: 48 h - Species: Daphnia magna) |
| ErC50 algae | 8 mg/l |
| NOEC Chronic Crustacea | 3.2 mg/l |
| Ammonium hydroxide (1336-21-6) | |
| LC50 Fish 1 | 8.2 mg/l (Exposure time: 96 h - Species: Pimephales promelas) |
| EC50 - Crustacea [1] | 0.66 mg/l (Exposure time: 48 h - Species: water flea) |
| NOEC Chronic Crustacea | 3.47 mg/l |
| Benzophenone (119-61-9) | |
| LC50 Fish 1 | 13.2 – 15.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through]) |
| ErC50 algae | 3.53 mg/l |
| NOEC Chronic Crustacea | 0.2 mg/l |
| Sodium carboxymethyl cellulose (9004-32-4) | |
| EC50 Other Aquatic Organisms 1 | 87.26 mg/l (Species: Ceriodaphnia dubia, Water flea) |
| Sodium chloride (7647-14-5) | |
| LC50 Fish 1 | 5560 (5560 – 6080) mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [flow-through]) |
| EC50 - Crustacea [1] | 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna) |
| LC50 Fish 2 | 12946 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static]) |
| EC50 - Crustacea [2] | 340.7 (340.7 – 469.2) mg/l (Exposure time: 48 h - Species: Daphnia magna [Static]) |
| NOEC Chronic Fish | 252 mg/l (Species: Pimephales promelas) |
| Ethanedial (107-22-2) | |
| LC50 Fish 1 | 215 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static]) |
| EC50 - Crustacea [1] | 404 mg/l (Exposure time: 48 h - Species: Daphnia magna) |
| 1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)- (77-99-6) | |
| EC50 - Crustacea [1] | 13000 mg/l (Exposure time: 48 h - Species: Daphnia species) |
| EC50 - Crustacea [2] | 10330 – 16360 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static]) |
| Petroleum distillates, hydrotreated light (64742-47-8) | |
| LC50 Fish 1 | 45 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through]) |
| LC50 Fish 2 | 2.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static]) |
| Naphtha, petroleum, hydrotreated heavy (64742-48-9) | |
| LC50 Fish 1 | 2200 mg/l (Exposure time: 96 h - Species: Pimephales promelas) |
| 2-Amino-2-methyl-1-propanol (124-68-5) | |
| LC50 Fish 1 | 190 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static]) |

12.2. Persistence and Degradability

| | |
|-------------------------------|------------------|
| Stolit Finish | |
| Persistence and Degradability | Not established. |

Stolit® X Finish

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| | |
|--------------------------------------|------------------------|
| Residual Monomers | |
| Persistence and Degradability | Readily biodegradable. |

12.3. Bioaccumulative Potential

| | |
|----------------------------------|------------------|
| Stolit Finish | |
| Bioaccumulative Potential | Not established. |

| | |
|--|---------------------------|
| 1,2-Benzisothiazol-3(2H)-one (2634-33-5) | |
| Partition coefficient n-octanol/water (Log Pow) | 0.99 (at 20 °C (at pH 5)) |

| | |
|--|----------------------------|
| 3(2H)-Isothiazolone, 2-methyl- (2682-20-4) | |
| Partition coefficient n-octanol/water (Log Pow) | -0.26 (at 20 °C (at pH 5)) |

| | |
|---|-------------------------|
| 3(2H)-Isothiazolone, 5-chloro-2-methyl- (26172-55-4) | |
| Partition coefficient n-octanol/water (Log Pow) | -0.71 – 0.75 (at 20 °C) |

| | |
|---|----------------------------|
| Silica, amorphous, diatomaceous earth (68855-54-9) | |
| BCF Fish 1 | (no known bioaccumulation) |

| | |
|--|------|
| Residual Monomers | |
| Partition coefficient n-octanol/water (Log Pow) | 0.93 |

| | |
|--|-----------|
| Benzophenone (119-61-9) | |
| BCF Fish 1 | 3.4 – 9.2 |
| Partition coefficient n-octanol/water (Log Pow) | 3.18 |

| | |
|------------------------------------|----------------------|
| Sodium chloride (7647-14-5) | |
| BCF Fish 1 | (no bioaccumulation) |

| | |
|--|-------------------------|
| Ethanedial (107-22-2) | |
| Partition coefficient n-octanol/water (Log Pow) | -1 (at 23 °C (at pH 5)) |

| | |
|--|----------------------|
| 1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)- (77-99-6) | |
| BCF Fish 1 | (0,14 dimensionless) |
| Partition coefficient n-octanol/water (Log Pow) | -0.47 (at 26 °C) |

| | |
|---|----------|
| Petroleum distillates, hydrotreated light (64742-47-8) | |
| BCF Fish 1 | 61 – 159 |

| | |
|--|-----------------------------|
| 2-Amino-2-methyl-1-propanol (124-68-5) | |
| BCF Fish 1 | (1 dimensionless) |
| Partition coefficient n-octanol/water (Log Pow) | -0.63 (at 20 °C (at pH >9)) |

12.4. Mobility in Soil

| | |
|---|----|
| Residual Monomers | |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | 15 |

12.5. Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

Ecology - Waste Materials: Avoid release to the environment.

Stolit® X Finish

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

14.1. In Accordance with DOT

Not regulated for transport

14.2. In Accordance with IMDG

Not regulated for transport

14.3. In Accordance with IATA

Not regulated for transport

14.4. In Accordance with TDG

Not regulated for transport

SECTION 15: REGULATORY INFORMATION**15.1. US Federal Regulations**

| | |
|--|---|
| Styrene-butadiene copolymer (9003-55-8) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active | |
| EPA TSCA Regulatory Flag | XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711). |
| 1,2-Benzisothiazol-3(2H)-one (2634-33-5) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active | |
| 3(2H)-Isothiazolone, 2-methyl- (2682-20-4) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active | |
| EPA TSCA Regulatory Flag | PMN - PMN - indicates a commenced PMN substance. SP - SP - indicates a substance that is identified in a proposed Significant New Uses Rule. |
| 3(2H)-Isothiazolone, 5-chloro-2-methyl- (26172-55-4) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active | |
| EPA TSCA Regulatory Flag | PMN - PMN - indicates a commenced PMN substance. SP - SP - indicates a substance that is identified in a proposed Significant New Uses Rule. |
| 2,2,4-Trimethyl-1,3-pentanediol diisobutyrate (6846-50-0) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active | |
| Silica, amorphous, diatomaceous earth (68855-54-9) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active | |
| Silica, cristobalite (14464-46-1) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active | |
| Ammonium hydroxide (1336-21-6) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active | |
| CERCLA RQ | 1000 lb |
| Benzophenone (119-61-9) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active | |
| Limestone (1317-65-3) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active | |
| Quartz (14808-60-7) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active | |
| Sodium carboxymethyl cellulose (9004-32-4) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active | |
| EPA TSCA Regulatory Flag | XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711). |
| Sodium chloride (7647-14-5) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active | |

Stolit® X Finish

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| |
|--|
| Ethanedial (107-22-2) |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active |
| 1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)- (77-99-6) |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active |
| Titanium dioxide (13463-67-7) |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active |
| Petroleum distillates, hydrotreated light (64742-47-8) |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active |
| Naphtha, petroleum, hydrotreated heavy (64742-48-9) |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active |
| Slack wax, petroleum (64742-61-6) |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active |
| 2-Amino-2-methyl-1-propanol (124-68-5) |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active |
| Kaolin (1332-58-7) |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active |

15.2. US State Regulations

California Proposition 65



WARNING: This product can expose you to Silica, cristobalite & quartz, Benzophenone, and Titanium Dioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

| Chemical Name (CAS No.) | Carcinogenicity | Developmental Toxicity | Female Reproductive Toxicity | Male Reproductive Toxicity |
|-----------------------------------|-----------------|------------------------|------------------------------|----------------------------|
| Silica, cristobalite (14464-46-1) | X | | | |
| Benzophenone (119-61-9) | X | | | |
| Quartz (14808-60-7) | X | | | |
| Titanium dioxide (13463-67-7) | X | | | |

| |
|---|
| Silica, amorphous, diatomaceous earth (68855-54-9) |
| U.S. - Pennsylvania - RTK (Right to Know) List |
| Silica, cristobalite (14464-46-1) |
| U.S. - New Jersey - Right to Know Hazardous Substance List |
| U.S. - Pennsylvania - RTK (Right to Know) List |
| U.S. - Massachusetts - Right To Know List |
| Ammonium hydroxide (1336-21-6) |
| U.S. - New Jersey - Right to Know Hazardous Substance List |
| U.S. - Pennsylvania - RTK (Right to Know) List |
| U.S. - Massachusetts - Right To Know List |
| U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List |
| Limestone (1317-65-3) |
| U.S. - New Jersey - Right to Know Hazardous Substance List |
| U.S. - Pennsylvania - RTK (Right to Know) List |
| U.S. - Massachusetts - Right To Know List |
| Quartz (14808-60-7) |
| U.S. - New Jersey - Right to Know Hazardous Substance List |
| U.S. - Pennsylvania - RTK (Right to Know) List |
| U.S. - Massachusetts - Right To Know List |
| Ethanedial (107-22-2) |
| U.S. - New Jersey - Right to Know Hazardous Substance List |
| Titanium dioxide (13463-67-7) |

Stolit® X Finish

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Massachusetts - Right To Know List

Perlite (93763-70-3)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Massachusetts - Right To Know List

2-Amino-2-methyl-1-propanol (124-68-5)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Massachusetts - Right To Know List

Mica (12001-26-2)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Massachusetts - Right To Know List

Kaolin (1332-58-7)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Massachusetts - Right To Know List

15.3. Canadian Regulations

Styrene-butadiene copolymer (9003-55-8)

Listed on the Canadian DSL (Domestic Substances List)

1,2-Benzisothiazol-3(2H)-one (2634-33-5)

Listed on the Canadian DSL (Domestic Substances List)

3(2H)-Isothiazolone, 2-methyl- (2682-20-4)

Listed on the Canadian DSL (Domestic Substances List)

3(2H)-Isothiazolone, 5-chloro-2-methyl- (26172-55-4)

Listed on the Canadian DSL (Domestic Substances List)

2,2,4-Trimethyl-1,3-pentanediol diisobutyrate (6846-50-0)

Listed on the Canadian DSL (Domestic Substances List)

Silica, amorphous, diatomaceous earth (68855-54-9)

Listed on the Canadian DSL (Domestic Substances List)

Silica, cristobalite (14464-46-1)

Listed on the Canadian DSL (Domestic Substances List)

Ammonium hydroxide (1336-21-6)

Listed on the Canadian DSL (Domestic Substances List)

Benzophenone (119-61-9)

Listed on the Canadian DSL (Domestic Substances List)

Limestone (1317-65-3)

Listed on the Canadian NDSL (Non-Domestic Substances List)

Quartz (14808-60-7)

Listed on the Canadian DSL (Domestic Substances List)

Sodium carboxymethyl cellulose (9004-32-4)

Listed on the Canadian DSL (Domestic Substances List)

Sodium chloride (7647-14-5)

Listed on the Canadian DSL (Domestic Substances List)

Ethanedial (107-22-2)

Listed on the Canadian DSL (Domestic Substances List)

Stolit® X Finish

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| |
|---|
| 1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)- (77-99-6) |
| Listed on the Canadian DSL (Domestic Substances List) |
| Titanium dioxide (13463-67-7) |
| Listed on the Canadian DSL (Domestic Substances List) |
| Petroleum distillates, hydrotreated light (64742-47-8) |
| Listed on the Canadian DSL (Domestic Substances List) |
| Naphtha, petroleum, hydrotreated heavy (64742-48-9) |
| Listed on the Canadian DSL (Domestic Substances List) |
| Perlite (93763-70-3) |
| Listed on the Canadian DSL (Domestic Substances List) |
| Slack wax, petroleum (64742-61-6) |
| Listed on the Canadian DSL (Domestic Substances List) |
| 2-Amino-2-methyl-1-propanol (124-68-5) |
| Listed on the Canadian DSL (Domestic Substances List) |
| Mica (12001-26-2) |
| Listed on the Canadian DSL (Domestic Substances List) |
| Kaolin (1332-58-7) |
| Listed on the Canadian DSL (Domestic Substances List) |

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Date of Preparation or Latest Revision : 07/29/2025

Revision

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products Regulations (HPR) SOR/2015-17. This product complies with US EPA (40 CFR 59) and South Coast AQMD (Rule 1113) VOC emission standards for architectural coatings. VOC less than 50 g/L.

GHS Full Text Phrases:

| | |
|------|---|
| H290 | May be corrosive to metals |
| H301 | Toxic if swallowed |
| H302 | Harmful if swallowed |
| H304 | May be fatal if swallowed and enters airways |
| H311 | Toxic in contact with skin |
| H314 | Causes severe skin burns and eye damage |
| H315 | Causes skin irritation |
| H317 | May cause an allergic skin reaction |
| H318 | Causes serious eye damage |
| H319 | Causes serious eye irritation |
| H330 | Fatal if inhaled |
| H332 | Harmful if inhaled |
| H335 | May cause respiratory irritation |
| H336 | May cause drowsiness or dizziness |
| H340 | May cause genetic defects |
| H341 | Suspected of causing genetic defects |
| H350 | May cause cancer |
| H351 | Suspected of causing cancer |
| H361 | Suspected of damaging fertility or the unborn child |
| H372 | Causes damage to organs through prolonged or repeated exposure |
| H373 | May cause damage to organs through prolonged or repeated exposure |

Stolit® X Finish

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| | |
|------|--|
| H400 | Very toxic to aquatic life |
| H401 | Toxic to aquatic life |
| H402 | Harmful to aquatic life |
| H410 | Very toxic to aquatic life with long lasting effects |
| H411 | Toxic to aquatic life with long lasting effects |
| H412 | Harmful to aquatic life with long lasting effects |

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

NA GHS SDS 2015 (Can, US)