

## SAFETY DATA SHEET

### SECTION 1 : IDENTIFICATION

Product identifier used on the label:

Product Name: Stolit 1.0 Dark Colors  
 Product Code: 82130  
 SDS Manufacturer Number: 82130

Other means of identification:

Synonyms: None.

Recommended use of the chemical and restrictions on use:

Product Use/Restriction: Waterbased Acrylic Coating.

Chemical manufacturer address and telephone number:

Manufacturer Name: Sto Corp.  
 Address: 6175 Riverside Drive, SW  
 Atlanta, Georgia 30331  
 General Phone Number: (404) 346-3666

Emergency phone number:

Emergency Phone Number: (800) 424-9300

### SECTION 2 : HAZARD(S) IDENTIFICATION

Classification of the chemical in accordance with CFR 1910.1200(d)(f):

GHS Pictograms:



Signal Word: WARNING.

GHS Class: Eye Irritation, Category 2.  
 Skin Irritation, Category 2.

Hazard Statements: Causes serious eye irritation.  
 Causes skin irritation.

Precautionary Statements: Wash hands thoroughly after handling.  
 Avoid release to the environment.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 IF ON SKIN: Wash with plenty of water.  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 Specific treatment (see ... on this label).  
 If skin irritation occurs: Get medical advice/attention.  
 If eye irritation persists: Get medical advice/attention.  
 Take off contaminated clothing and wash it before reuse.  
 Collect spillage.  
 Dispose of contents/container in accordance with Local, State, Federal and Provincial regulations.

Hazards not otherwise classified that have been identified during the classification process:

Route of Exposure: Eyes. Skin. Inhalation. Ingestion.

Potential Health Effects:

Eye: May cause irritation.

Skin: May cause irritation.

Inhalation: Prolonged or excessive inhalation may cause respiratory tract irritation.

Ingestion: Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Target Organs: Eyes. Skin. Respiratory system. Digestive system.

### SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures:

Chemical Name	CAS#	Ingredient Percent	EC Num.
---------------	------	--------------------	---------

Acrylic polymer	No Data	10 - 30 by weight	
-----------------	---------	-------------------	--

Barium sulfate	7727-43-7	5 - 10 by weight	231-784-4
Calcium carbonate	1317-65-3	30 - 60 by weight	215-279-6
Crystalline silica (Quartz)	14808-60-7	1 - 5 by weight	238-878-4
Perlite	93763-70-3	1 - 5 by weight	
Water	7732-18-5	10 - 30 by weight	231-791-2

## SECTION 4 : FIRST AID MEASURES

### Description of necessary measures:

<b>Eye Contact:</b>	Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Get immediate medical attention.
<b>Skin Contact:</b>	Immediately wash skin with plenty of soap and water for 15 to 20 minutes, while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists.
<b>Inhalation:</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.
<b>Ingestion:</b>	If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

### Most important symptoms/effects, acute and delayed:

**Other First Aid:** First Responders should provide for their own safety prior to rendering assistance.

## SECTION 5 : FIRE FIGHTING MEASURES

### Suitable and unsuitable extinguishing media:

<b>Suitable Extinguishing Media:</b>	Use dry chemical or foam when fighting fires involving this material. Water mist may be used to cool closed containers.
<b>Unusual Fire Hazards:</b>	Material may spatter above 100 °C/212 °F.

### Special protective equipment and precautions for fire-fighters:

<b>Protective Equipment:</b>	As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) and full protective gear.
<b>Fire Fighting Instructions:</b>	Evacuate area of unprotected personnel. Use cold water spray to cool fire exposed containers to minimize risk of rupture. Do not enter confined fire space without full protective gear. If possible, contain fire run-off water.

### NFPA Ratings:

NFPA Flammability:	1
NFPA Reactivity:	0



NFPA Health: 1

## SECTION 6 : ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures:

**Personal Precautions:** Evacuate area and keep unnecessary and unprotected personnel from entering the spill area.

### Environmental precautions:

**Environmental Precautions:** Avoid runoff into storm sewers, ditches, and waterways.

### Methods and materials for containment and cleaning up:

<b>Methods for containment:</b>	Contain spills with an inert absorbent material such as soil, sand or oil dry.
<b>Methods for cleanup:</b>	Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Provide ventilation. Clean up spills immediately observing precautions in the protective equipment section.

## SECTION 7 : HANDLING and STORAGE

### Precautions for safe handling:

<b>Handling:</b>	Use with adequate ventilation. Avoid breathing vapor, aerosol or mist.
<b>Hygiene Practices:</b>	Wash thoroughly after handling.

### Conditions for safe storage, including any incompatibilities:





