



81272-750 StoGuard[®] Transition Membrane

Sto Corp.
3800 Camp Creek Pkwy
Building 1400, Suite 120
Atlanta, GA 30331, USA
Tel: (404) 346-3666
Toll Free: (800) 221-2397
Fax: (404) 346-3119
www.stocorp.com

A flexible air barrier material specially designed for use with StoGuard waterproof coatings including Sto Gold[®] Coat, StoEmerald[®] Coat and Sto VaporSeal[™]. It is used at detail areas to provide flexible connections to achieve continuity of the air barrier assembly.

Contents	1 roll
Contenido	1 rollo
Width	4.75"
Anchura	12 cm
Length	164 ft.
Longitud	50 m

For application instructions and more detailed information, please refer to the product bulletin and MSDS at www.stocorp.com
Rev. 00 02/2013

Storage
Store in a dry area. Protect from excess heat, cold, and direct sunlight.

ATTENTION:
This product is intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. It should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all liability for on-site inspections, for its products applied improperly, and assumes no liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the job-performance of adjacent building components or assemblies, or for other construction activities beyond Sto's control. Improper use of this product or use as part of an improperly designed or constructed large structure of the building or its components. **STO CORP. DISCLAIMS ALL WARRANTIES EXPRESSED OR IMPLIED EXCEPT FOR EXPLICIT LIMITED WRITTEN WARRANTIES ISSUED TO AND ACCEPTED BY BUILDING OWNERS IN ACCORDANCE WITH STO'S WARRANTY PROGRAMS WHICH ARE SUBJECT TO CHANGE FROM TIME TO TIME.** For the latest, most current warranties, cautions and disclaimers, please refer to the Sto Corp. website, www.stocorp.com

StoGuard[®] Transition Membrane

Flexible air barrier membrane

StoGuard[®] Transition Membrane is a flexible air barrier membrane for use on vertical above grade wall construction over properly prepared concrete, concrete masonry (CMU), glass mat gypsum sheathing and Exterior or Exposure I wood-based sheathing. It is used with StoGuard waterproof air barrier membranes including Sto Gold Coat[®], Sto EmeraldCoat[®], Sto AirSeal[™], Sto VaporSeal[™] and Sto ExtraSeal[™]. It is used at detail areas to provide flexible connections to achieve continuity of the air barrier assembly. It also functions as a secondary weather seal at joints in construction.

