


StoQuik® Silver DrainScreen™ "L" Bead Termination Accessory at Dissimilar Material

Detail No.: 11.03a DS

Date: January 2015



Notes:

1. Use the "L" Bead Accessory
 - a. Terminations at windows and doors.
(See Sto Detail 11.25a)
 - b. Terminations at dissimilar materials.
(See Sto Detail 11.50a)
 - c. Back-to-back at expansion joints.
(See Sto Detail 11.50a).
 - d. Window/door head in combination with flashing.
(See Sto Detail 11.23a)
 - e. Floor line (in combination with flashing).
(See Sto Detail 11.41a)
2. Use spray adhesive (3M Super 77 or 3M Super 90) applied to the cement board to temporarily hold the accessory in place. Place StoGuard Mesh over perforated front flange of accessory. Skim coat StoGuard Mesh with Sto base coat and allow to dry. When installing Sto Mesh, embed Sto Mesh in Sto base coat and overlap StoGuard Mesh to terminating bead of accessory.
3. Refer to Sto Specification QS 200 DS for complete information on design requirements, installation, and accessories.

ATTENTION

Sto products are intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. They should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all, and assumes no, liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, or for other construction activities beyond Sto's control. Improper use of Sto products or use as part of an improperly designed or constructed larger assembly or building may result in serious damage to Sto products, and to the structure of the building or its components.

STO CORP. DISCLAIMS ALL WARRANTIES EXPRESSED OR IMPLIED EXCEPT FOR EXPLICIT LIMITED WRITTEN WARRANTIES ISSUED TO AND ACCEPTED BY BUILDING OWNERS IN ACCORDANCE WITH STO'S WARRANTY PROGRAMS WHICH ARE SUBJECT TO CHANGE FROM TIME TO TIME. For the fullest, most current information on proper application, clean-up, mixing and other specifications and warranties, cautions and disclaimers, please refer to the Sto Corp. website, www.stocorp.com.

www.stocorp.com