


StoTherm® ci Over Masonry Window Sill/Jamb: Rough Opening Protection and Pan Flashing with Window Installed

Detail No.: 19.26a2
Date: February 2019



Notes:

- 1) Provide gap for continuous exterior perimeter weather seal.
- 2) Provide gap for continuous interior perimeter air seal.
- 3) Consult with window and sealant manufacturers to verify installation detailing.
- 4) See Sto detail 19.26a1 for rough opening protection and pan flashing at sill. See Sto detail 19.24a1 and 19.24a2 for protection at head. See Sto detail 19.26a3 for complete sill/jamb assembly.
- 5) Test the final assembly using materials and sub-trades associated with the project to verify performance.

IMPORTANT: Components not identified as Sto are furnished by other manufacturers and are not necessarily installed by trades who install the Sto products. Refer to project specific contract documents.

www.stocorp.com

ATTENTION

Sto products are intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. They should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all, and assumes no, liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, or for other construction activities beyond Sto's control. Improper use of Sto products or use as part of an improperly designed or constructed larger assembly or building may result in serious damage to Sto products, and to the structure of the building or its components.

STO CORP. DISCLAIMS ALL WARRANTIES EXPRESSED OR IMPLIED EXCEPT FOR EXPLICIT LIMITED WRITTEN WARRANTIES ISSUED TO AND ACCEPTED BY BUILDING OWNERS IN ACCORDANCE WITH STO'S WARRANTY PROGRAMS WHICH ARE SUBJECT TO CHANGE FROM TIME TO TIME. For the fullest, most current information on proper application, clean-up, mixing and other specifications and warranties, cautions and disclaimers, please refer to the Sto Corp. website, www.stocorp.com.

