

StoTherm® ci

Sill Flashing: Brick Mold Window over Wood Frame

Detail No.: 2.26

Date: January 2015

Step 1

Install a ribbon of sealant over the StoGuard® Waterproofing/Air Barrier

Step 2

Immediately press the sill flashing into the wet sealant and allow sealant to cure

Position of window shown in red

Step 3

Install StoGuard® Detail Component lapping over end dams of the flashing

Step 4

Install window

Install air seal

Install cladding

Notes:

Step 1

- 1] Install sealant to provide an air seal between the StoGuard and pan flashing.

Step 2

- 2] Press the pan flashing into place and, if necessary, fasten through the wet sealant.

Step 3

- 3] Install StoGuard Detail Component over the enddam of the flashing so water draining down the jamb will be directed into the pan flashing. See details 20.20F and 20.20R for alternate options.

Step 4

- 4] Install the window and seal the interior perimeter with an air seal.
- 5] Install the cladding and provide a seal between the head and jambs of the window. Allow water to drain from the sill.

IMPORTANT: Components not identified as Sto are furnished by other manufacturers and are not necessarily installed by trades who install the Sto products. Refer to project specific contract documents.

Property of Sto Corp. All Rights Reserved.

Attention

Sto products are intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. They should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all, and assumes no, liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, or for other construction activities beyond Sto's control. Improper use of Sto products or use as part of an improperly designed or constructed larger assembly or building may result in serious damage to Sto products, and to the structure of the building or its components. **STO CORP. DISCLAIMS ALL WARRANTIES EXPRESS OR IMPLIED EXCEPT FOR EXPLICIT LIMITED WRITTEN WARRANTIES ISSUED TO AND ACCEPTED BY BUILDING OWNERS IN ACCORDANCE WITH STO'S WARRANTY PROGRAMS WHICH ARE SUBJECT TO CHANGE FROM TIME TO TIME.** For the fullest, most current information on proper application, clean-up, mixing and other specifications and warranties, cautions and disclaimers, please refer to the Sto Corp. website, www.stocorp.com.

www.stocorp.com