

## StoTherm® ci Inside and Outside Corner with Common Substrate and Sto Mesh Reinforcement

### Detail No.: 52s.54B Date: November 2015

# StoGuard® Joint Treatment Sto Adhesive Light Gauge Steel Stud Framing Sheathing-Sto EPS -Insulation Board StoGuard® Air and Moisture Barrier Sto Base Coat (with Sto Mesh Embedded) Sto Primer (Optional) Sto Finish -Return Sto Mesh 6 in. min. @ Inside Corner Sto Mesh Return Sto Mesh 6 in. min. Around Corner

### Notes:

- 1. Provide joint at interior corner if movement is anticipated. Refer to Sto Detail 52s.53.
- Refer to StoTherm ci System Bulletins and Specifications, Sto Product Bulletins, Tech Hotlines, and Sto Installation and Maintenance Guides for complete information.
- Refer to applicable ICC or CCMC Evaluation Reports for building code compliance information.

**IMPORTANT:** Components not identified as Sto are furnished by other manufacturers and are not necessarily installed by trades who install Sto products. Refer to project specific contract documents.

#### **ATTENTION**

Sto products are intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. They should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all, and assumes no, liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, of for other construction activities beyond Sto's control. Improper use of Sto products or use as part of an improperly designed or constructed larger assembly or building may result in serious damage to Sto products, and to the structure of the building or its components.

Property of Sto Corp. All Rights Reserved

www.stocorp.com