




Building with conscience.

StoVentro™ Sub-Construction System
StoVentro Steel Bracket 25mm (1 inch)


Date: October 2025

Detail No.: 90.Sc.003


To achieve a system depth of ~1 inch with 25mm (1 in.) brackets, an L or T rail with a 1 in. or shorter leg is required.




25mm StoVentro Bracket





25mm Bracket with example 1-inch L-angle



StoVentro Steel - 25mm (1 inch)
Large Bracket (FP)



StoVentro Steel - 25mm (1 inch)
Small Bracket (GP)



StoVentro Thermal
Blocking Elements
6mm ($\frac{1}{4}$ ") thickness

ATTENTION

Sto products are intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. They should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all, and assumes no, liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, or for other construction activities beyond Sto's control. Improper use of Sto products or use as part of an improperly designed or constructed larger assembly or building may result in serious damage to Sto products, and to the structure of the building or its components.

STO CORP. DISCLAIMS ALL WARRANTIES EXPRESSED OR IMPLIED EXCEPT FOR EXPLICIT LIMITED WRITTEN WARRANTIES ISSUED TO AND ACCEPTED BY BUILDING OWNERS IN ACCORDANCE WITH STO'S WARRANTY PROGRAMS WHICH ARE SUBJECT TO CHANGE FROM TIME TO TIME. For the fullest, most current information on proper application, clean-up, mixing and other specifications and warranties, cautions and disclaimers, please refer to the Sto Corp. website, www.stocorp.com.