


StoQuik® Finish System for Insulated Concrete Forms (ICF) Interior Foundation Protection

Detail No.: 17.10
Date: November 2022



Notes:

1. Refer to System Specifications and System Bulletin for more information and design guidance on wall assembly components.
2. Allow the concrete slab to cure for 7 (minimum) to 28 days. Install an application of Sto Watertight Coat* to the prepared concrete around the perimeter of the foundation sealing around the reinforcing bars set in the foundation.
3. Install the ICF wall, pouring the concrete onto the Sto Watertight Coat. Sto Flexyl is an acceptable substitute for Sto Watertight Coat.
4. Allow the concrete in the ICF to cure for a minimum 28 days.
5. Install a second application of Sto Watertight Coat and Sto Detail Mesh over the initial application and up the wall to the desired height. Use a sealant bead at the base of the wall.
6. Provide protection board and drainage around foundation perimeter.
7. Components not identified as Sto are furnished by other manufacturers and are not necessarily installed by trades who install the Sto products. Refer to project specific contract documents.

ATTENTION

Property of Sto Corp. All Rights Reserved.

www.stocorp.com

Sto products are intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. They should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all, and assumes no, liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, or for other construction activities beyond Sto's control. Improper use of Sto products or use as part of an improperly designed or constructed larger assembly or building may result in serious damage to Sto products, and to the structure of the building or its components.

STO CORP. DISCLAIMS ALL WARRANTIES EXPRESSED OR IMPLIED EXCEPT FOR EXPLICIT LIMITED WRITTEN WARRANTIES ISSUED TO AND ACCEPTED BY BUILDING OWNERS IN ACCORDANCE WITH STO'S WARRANTY PROGRAMS WHICH ARE SUBJECT TO CHANGE FROM TIME TO TIME. For the fullest, most current information on proper application, clean-up, mixing and other specifications and warranties, cautions and disclaimers, please refer to the Sto Corp. website, www.stocorp.com.

