



Building with conscience.

Sto Corp.

3800 Camp Creek Parkway

Building 1400, Suite 120

Atlanta, GA 30331

Tel: 404-346-3666

Toll Free: 1-800-221-2397

Fax: 404-346-3119

www.stocorp.com

Sto Guide Specification No. F477
Sto Interior Finish System for Pool Rooms

Section 09 94 13
TEXTURED FINISHING

Notes in italics, such as this one, are explanatory and intended to guide the design/construction professional and user in the proper selection and use of materials. This specification should be modified where necessary to accommodate individual project conditions.

Table of Contents

PART 1	GENERAL	3
1.1	SUMMARY	3
1.2	SUBMITTALS.....	3
1.3	REFERENCES.....	3
1.4	QUALITY ASSURANCE	3
1.5	DELIVERY, STORAGE AND HANDLING	3
1.6	WARRANTY	4
PART 2	PRODUCTS	4
2.1	MATERIALS	4
PART 3	EXECUTION	4
3.1	INSTALLATION.....	4

PART 1 GENERAL

1.1 SUMMARY

- A. Provide textured finish system for interior pool room walls and ceiling over compatible interior wall board and ceiling substrates specially designed for pool room applications.

IMPORTANT: This guide specification covers installation of a Class A textured finish system over building code compliant wall and ceiling construction. It does not address air sealing, ventilation, and other important aspects of design that must be taken into consideration for high humidity areas such as pool rooms. Consult with a qualified design professional for overall design of the wall and ceiling assembly and mechanical engineering of the pool room space. Where necessary conduct dynamic hygrothermal modeling to evaluate and verify the performance of the final design.

1.2 SUBMITTALS

- A. Product Data: Submit manufacturer's product data and installation instructions for each material and product used. Include manufacturer's Material Safety Data Sheets.

1.3 REFERENCES

- A. South Coast Air Quality Management District (SCAQMD)
Rule 1113 Architectural Coatings

1.4 QUALITY ASSURANCE

- A. Manufacturer's Qualifications: The textured finish system manufacturer shall be a company with at least thirty five years of experience in manufacturing specialty finishes and regularly engaged in the manufacture and marketing of products specified herein. The manufacturer shall have an ISO 9001:2008 certified quality system and ISO 14001:2004 certified environmental management system.
- B. Installer's Qualifications: The contractor shall be qualified to perform the work specified by reason of experience. Contractor shall have at least 5 years of experience in commercial textured finish application, and shall have completed at least 3 projects of similar size and complexity. Contractor shall provide proof before commencement of work that he/she will maintain and supervise a qualified crew of applicators through the duration of the work. When requested Contractor shall provide a list of the last three comparable jobs including the name, location, and start and finish dates for the work.
- C. Mock-ups: The contractor shall install a mock-up of the system for evaluation and approval by the design professional, building owner, or owner's representative/quality assurance agent.
- D. Testing: Testing shall be conducted as directed by the design professional, building owner, or owner's representative/quality assurance agent to verify wall/ceiling assembly performance and to verify adhesion to prepared substrates before and during construction.

1.5 DELIVERY, STORAGE AND HANDLING

- A. Deliver products in original packaging, labeled with product identification, manufacturer, and batch number.
- B. Store products in a dry area with temperature maintained between 50 and 85 degrees F (10 and 29 degrees C). Protect from direct sunlight. Protect from freezing. Protect from extreme heat (>90 degrees F [32 degrees C]).
- C. Handle products in accordance with manufacturer's printed instructions.

1.6 WARRANTY

- A. Provide manufacturer's standard limited warranty.

PART 2 PRODUCTS

2.1 MATERIALS

- A. Textured Finishes (*select one*)
 - 1. Stolit – high performance decorative and protective acrylic-based textured wall finish with integral color, complies with SCAQMD Rule 1113 for architectural finishes.
 - 2. Sto Essence DPR – high performance decorative and protective textured wall finish with integral color, complies with SCAQMD Rule 1113 for architectural finishes.
- B. StoSignature Finishes – Stolit acrylic based textured wall finish applied over Sto Crack Defense with specialized techniques to achieve unique textures, impressions or effects. Refer to www.stocorp.com for StoSignature Finishes Brochure and Installation Guides.
- C. StoCast Finishes – Sto custom cast pre-formed decorative and protective finish and adhesive
 - 1. StoCast Wood
 - 2. StoCast Brick
- D. Primer
 - 1. Sto Primer – acrylic-based sanded primer, complies with SCAQMD Rule 1113 for primers.
- E. Waterproof Base Coat (*select one*)
 - 1. Sto Flexyl – one component acrylic-based additive combined with portland cement, complies with SCAQMD Rule 1113 for waterproofing sealers.
 - 2. Sto Watertight Coat – two component acrylic-based additive with dry ingredient, complies with SCAQMD Rule 1113 for waterproofing sealers.
- F. Surface Reinforcement
 - 1. Sto Mesh – nominal 4.5 oz/sq.yd. (153 g/sq.m.) glass fiber reinforcing mesh treated for compatibility with Sto materials
- G. Interior Pool Room Wallboard (select one)
 - 1. PermaBase® Brand cement board as manufactured by National Gypsum

2. DensShield® Tile Backer as manufactured by Georgia-Pacific
3. Diamondback® Tile Backer as manufactured by CertainTeed
4. Durock® Brand cement board as manufactured by USG
5. Durock™ Brand Tile Backer as manufactured by USG

PART 3 EXECUTION

3.1 INSTALLATION

- A. General Surface Preparation Wall board and ceiling substrates must be clean, dry, and free of surface contamination. Wall board and ceiling substrates must be installed in conformance with the manufacturer's written installation instructions, except joint taping and spotting of fasteners with joint compound are not required. Accessories such as corner beads must be corrosion proof and with perforated flanges for keying of the base coat.
- B. Mixing
 1. Mix Sto products in accordance with published literature. Refer to applicable Product Bulletins for specific information on use, handling, application, precautions, and limitations of specific products.
- C. Application
 1. Install corrosion resistant termination accessories at junctures with penetrations such as pipes, electrical fixtures, and window and door openings. Refer to Sto Guide details.
 2. Install nominal 1/8 inch (3 mm) base coat by trowel to the wall or ceiling surface. Work horizontally or vertically in strips of 40 inches (1016 mm), and immediately embed the mesh into the wet base coat by troweling from the center to the edge of the mesh. Overlap mesh not less than 2-½ inches (64 mm) at mesh seams and feather at seams. Double wrap all inside and outside corners with minimum 8-inch (203 mm) overlap in each direction (if accessories are NOT used at these locations). Avoid wrinkles in the mesh. The mesh must be fully embedded so that no mesh color shows through the base coat when it is dry. Re-skim with additional base coat if mesh color is visible. Where accessories are used overlap perforated flanges of accessories with the base coat/reinforcing mesh application. Do not install base coat and mesh onto solid (unperforated) portions of accessories.
 3. When the base coat application is dry apply the primer by brush or roller to the entire base coat surface.
 4. Textured Finish Application - when the primer application is dry apply the textured finish by trowel. Apply finish in a continuous application, and work to a wet edge. Float the finish to achieve the desired texture. Refer to the applicable product bulletin,
 5. StoSignature Finish Application – refer to StoSignature Application Guide
 6. Sto Custom Cast Finish Application – refer to applicable Application Guide and/or Product Bulletin for selected finish
- D. Protection
 1. Provide protection of installed materials from water infiltration into or behind them.
 2. Provide protection of installed materials from dust, dirt, precipitation, freezing and continuous high humidity until they are fully dry.

3. Seal penetrations, seams, gaps, cracks, and other discontinuities in the finished wall and ceiling surfaces to prevent air leakage towards the exterior or adjacent spaces.

ATTENTION

Sto products are intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. They should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all, and assumes no, liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, or for other construction activities beyond Sto's control. Improper use of Sto products or use as part of an improperly designed or constructed larger assembly or building may result in serious damage to Sto products, and to the structure of the building or its components. **STO CORP. DISCLAIMS ALL WARRANTIES EXPRESS OR IMPLIED EXCEPT FOR EXPLICIT LIMITED WRITTEN WARRANTIES ISSUED TO AND ACCEPTED BY BUILDING OWNERS IN ACCORDANCE WITH STO'S WARRANTY PROGRAMS WHICH ARE SUBJECT TO CHANGE FROM TIME TO TIME.** For the fullest, most current information on proper application, clean-up, mixing and other specifications and warranties, cautions and disclaimers, please refer to the Sto Corp. website, www.stocorp.com.