

Detail No.: **51.55**

Date: **November 2025**

Page: **1 of 2**

Notes:

1. StoPanel® Brick ci is a lightweight energy efficient pre-fabricated exterior wall panel with extruded polystyrene (XPS) insulation, continuous air and water-resistive barrier (AWRB), and can be finished with a wide variety of masonry veneer options.

2. Alternative air and water resistive barriers (AWRB): Sto Gold Coat®, Sto AirSeal®, and StoGuard® VaporSeal.

3. Alternative Edge and Joint Treatment: Sto RapidGuard®

4. Z-Clip Furring and metal Perimeter Channel set in wet Sto RapidGuard®. Cover fastener heads with dab of Sto RapidGuard®.

5. Alternatives:

XPS Insulation: ASTM C 578, Type IV compliant.

Mineral Wool or Stone Wool Insulation as listed by Sto Corp. Refer to specifications for more information.

6. Minimum 3.4 lb./yd² self-furred galvanized steel diamond mesh metal lath in compliance with ASTM C 847.

7. Components not identified as Sto are furnished by other manufacturers.

ATTENTION


Property of Sto Corp. All Rights Reserved.

www.stopanel.com

Sto products are intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. They should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all, and assumes no, liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, or for other construction activities beyond Sto's control. Improper use of Sto products or use as part of an improperly designed or constructed larger assembly or building may result in serious damage to Sto products, and to the structure of the building or its components.

STO CORP. DISCLAIMS ALL WARRANTIES EXPRESSED OR IMPLIED EXCEPT FOR EXPLICIT LIMITED WRITTEN WARRANTIES ISSUED TO AND ACCEPTED BY BUILDING OWNERS IN ACCORDANCE WITH STO'S WARRANTY PROGRAMS WHICH ARE SUBJECT TO CHANGE FROM TIME TO TIME. For the fullest, most current information on proper application, clean-up, mixing and other specifications and warranties, cautions and disclaimers, please refer to the Sto Corp. website, www.stocorp.com.





Detail No.: **51.55**

Date: **November 2025**

Page: **2 of 2**

Notes:

1. StoPanel® Brick ci is a lightweight energy efficient pre-fabricated exterior wall panel with extruded polystyrene (XPS) insulation, continuous air and water-resistant barrier (AWRB), and can be finished with a wide variety of masonry veneer options.

2. Alternative air and water resistive barriers (AWRB): Sto Gold Coat®, Sto AirSeal®, and StoGuard® VaporSeal.

3. Alternative Edge and Joint Treatment: Sto RapidGuard®

4. Z-Clip Furring and metal Perimeter Channel set in wet Sto RapidGuard®. Cover fastener heads with dab of Sto RapidGuard®.

5. Alternatives:

XPS Insulation: ASTM C 578, Type IV compliant.

Mineral Wool or Stone Wool Insulation as listed by Sto Corp. Refer to specifications for more information.

6. Minimum 3.4 lb./yd² self-furred galvanized steel diamond mesh metal lath in compliance with ASTM C 847.

7. Components not identified as Sto are furnished by other manufacturers.

ATTENTION

Property of Sto Corp. All Rights Reserved.

www.stopanel.com

Sto products are intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. They should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all, and assumes no, liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, or for other construction activities beyond Sto's control. Improper use of Sto products or use as part of an improperly designed or constructed larger assembly or building may result in serious damage to Sto products, and to the structure of the building or its components.

STO CORP. DISCLAIMS ALL WARRANTIES EXPRESSED OR IMPLIED EXCEPT FOR EXPLICIT LIMITED WRITTEN WARRANTIES ISSUED TO AND ACCEPTED BY BUILDING OWNERS IN ACCORDANCE WITH STO'S WARRANTY PROGRAMS WHICH ARE SUBJECT TO CHANGE FROM TIME TO TIME. For the fullest, most current information on proper application, clean-up, mixing and other specifications and warranties, cautions and disclaimers, please refer to the Sto Corp. website, www.stocorp.com.

