

StoPowerwall® ExtraSeal® Parapet - Front

ATTENTION

Metal Parapet Coping Blocking Cleat with Sealant Fully Adhered Waterproof Membrane Note: Stop at edges of perforated flange of accessory Casing Beads Accessory by others (See Note 6) Sto ExtraSeal® Skim Coat Water-Resistive Air Barrier (See Note 1) Structural Floor Line Sto RapidGuard® or StoGuard® Backer Rod Conformable Membrane & Sealant (Stop at edges of perforated flange of accessory) Sto Primer (Optional - See Note 5) Horizontal Movement Joint at Underside of Structure Sto Powerwall® Brown Coat (See Note 3) Control Joint Accessory by others (See Note 6) Sto ExtraSeal®Scratch Coat StoGuard® Casing Beads Conformable Membrane Accessory by others Note: Stop at edges of perforated flange (See Note 6) of accessory (See Note 1)

Detail No.: 65c.81 Date: January 2025 Page 1 of 2

Notes:

- 1. Refer to StoGuard Product Use Chart (Table 1.1) for StoGuard detail components; joint treatment, rough opening protection, backing for masonry anchors, or transitions to dissimilar materials, joints and seams in construction.
- 2. Refer to General Notes for specific information and design guidance on wall assembly components.
- 3. Stucco brown coat material in compliance with ASTM C926 and manufactured or listed by Sto Corp.
- 4. Refer to applicable Sto guide specifications, product bulletins, Tech Hotlines, and other Sto guide details for additional information.
- 5. Sto Primer is required for Sto Specialty Finishes such as Sto GraniTex, StoSignature Brick, and others. Refer to specific Sto finish product bulletins.
- 6. Components not identified as Sto are furnished by other manufacturers and are not necessarily installed by trades who install the Sto products. Refer to project specific contract documents.

Property of Sto Corp. All Rights Reserved.

Sto products are intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. They should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all, and assumes no, liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, of for other construction activities beyond Sto's control. Improper use of Sto products or use as part of an improperly designed or constructed larger assembly or building may result in serious damage to Sto products, and to the structure of the building or its components.

STO CORP. DISCLAIMS ALL WARRANTIES EXPRESSED OR IMPLIED EXCEPT FOR EXPLICIT LIMITED WRITTEN WARRANTIES ISSUED TO AND ACCEPTED BY BUILDING OWNERS IN ACCORDANCE WITH STO'S WARRANTY PROGRAMS WHICH ARE SUBJECT TO CHANGE FROM TIME TO TIME. For the fullest, most current information on proper application, clean-up, mixing and other specifications and warranties, cautions and disclaimers, please refer to the Sto Corp. website, www.stocorp.com.

www.stocorp.com





StoPowerwall® ExtraSeal® Parapet - Back

ATTENTION

Blocking Sto ExtraSeal® Skim Coat Cleat Water-Resistive Air Barrierwith Sealant (See Note 1) Metal Parapet Coping Fully Adhered Waterproof Membrane Cover Board Roof Structure Roof Insulation Vapor Control Membrane Roof Perimeter (Permeance as Determined by Barrier Layer Qualified Professional)

Detail No.: 65c.81 Date: January 2025 Page 2 of 2

Notes:

- 1. Refer to StoGuard Product Use Chart (Table 1.1) for StoGuard detail components; joint treatment, rough opening protection, backing for masonry anchors, or transitions to dissimilar materials, joints and seams in construction.
- 2. Refer to General Notes for specific information and design guidance on wall assembly components.
- 3. Stucco brown coat material in compliance with ASTM C926 and manufactured or listed by Sto Corp.
- 4. Refer to applicable Sto guide specifications, product bulletins, Tech Hotlines, and other Sto guide details for additional information.
- 5. Sto Primer is required for Sto Specialty Finishes such as Sto GraniTex, StoSignature Brick, and others. Refer to specific Sto finish product bulletins.
- 6. Components not identified as Sto are furnished by other manufacturers and are not necessarily installed by trades who install the Sto products. Refer to project specific contract documents.

Property of Sto Corp. All Rights Reserved.

Sto products are intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. They should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all, and assumes no, liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, of for other construction activities beyond Sto's control. Improper use of Sto products or use as part of an improperly designed or constructed larger assembly or building may result in serious damage to Sto products, and to the structure of the building or its components.





www.stocorp.com