




StoPowerwall® Buildouts

Detail No.: 4.70

Date: December 2015



Notes:

- 1] Install foam shapes over StoPowerwall stucco using Sto adhesive.
- 2] Cover the shapes with Sto base coat and reinforcing mesh lapping onto the face of the stucco a minimum of 2.5" (65 mm).
- 3] The exposed surface must have a minimum slope of 1:2 (27°). In locations where ice and snow may accumulate increase slope.
- 4] Provide Sto Flexyl and mesh on upper surfaces of buildouts projecting more than 2" (50 mm) from the stucco surface lapping over the base coat and stucco to provide a weather tight seal.
- 5] Consult local building code requirements for maximum allowable foam thickness
- 6] Apply Sto Primer over all surfaces to provide a uniform color base for the Sto finish.

IMPORTANT: Components not identified as Sto are furnished by other manufacturers and are not necessarily installed by trades who install the Sto products. Refer to project specific contract documents.

Attention

Sto products are intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. They should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all, and assumes no, liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, or for other construction activities beyond Sto's control. Improper use of Sto products or use as part of an improperly designed or constructed larger assembly or building may result in serious damage to Sto products, and to the structure of the building or its components. **STO CORP. DISCLAIMS ALL WARRANTIES EXPRESS OR IMPLIED EXCEPT FOR EXPLICIT LIMITED WRITTEN WARRANTIES ISSUED TO AND ACCEPTED BY BUILDING OWNERS IN ACCORDANCE WITH STO'S WARRANTY PROGRAMS WHICH ARE SUBJECT TO CHANGE FROM TIME TO TIME.** For the fullest, most current information on proper application, clean-up, mixing and other specifications and warranties, cautions and disclaimers, please refer to the Sto Corp. website, www.stocorp.com.

www.stocorp.com