




StoPowerwall® Brick Mold Window Head

Detail No.: 5.20

Date: December 2015



Notes:

- 1] Protect the rough opening from water penetration by wrapping with StoGuard® as per Sto detail 5.09. Direct any water penetration to the exterior at or above the sill flashing (Refer to Sto details 5.21 and 5.22.)
- 2] Provide head flashing over the window to direct water away from the window. Fold flashing over the window head - jamb interface.
- 3] Provide continuous air barrier around the interior perimeter of the window to reduce: leaking, condensation related to air movement, and sound and insect intrusion.
- 4] Install expansion joint at the corner of the opening to allow for the release of stresses in the stucco.

IMPORTANT: Components not identified as Sto are furnished by other manufacturers and are not necessarily installed by trades who install the Sto products. Refer to project specific contract documents.

Property of Sto Corp. All Rights Reserved.

Attention

Sto products are intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. They should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all, and assumes no, liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, or for other construction activities beyond Sto's control. Improper use of Sto products or use as part of an improperly designed or constructed larger assembly or building may result in serious damage to Sto products, and to the structure of the building or its components. **STO CORP. DISCLAIMS ALL WARRANTIES EXPRESS OR IMPLIED EXCEPT FOR EXPLICIT LIMITED WRITTEN WARRANTIES ISSUED TO AND ACCEPTED BY BUILDING OWNERS IN ACCORDANCE WITH STO'S WARRANTY PROGRAMS WHICH ARE SUBJECT TO CHANGE FROM TIME TO TIME.** For the fullest, most current information on proper application, clean-up, mixing and other specifications and warranties, cautions and disclaimers, please refer to the Sto Corp. website, www.stocorp.com.

www.stocorp.com