

StoPowerwall® ExtraSeal® Frame to CMU at Floor Line

ATTENTION

Batt Insulation Wood Sheathing Wood Frame StoGuard® Air & Water-Resistive Barrier (See Note 1) Code Compliant Paper or Felt WRB (Water-resistive barrier) Sto DrainScreen® Galvanized StoGuard® Self-Furred Conformable Diamond Mesh Membrane or (Expanded Metal Lath) Sto RapidGuard® Sto Powerwall® Scratch Coat (See Note 3) Sto Powerwall® Brown Coat (See Note 3) Casing Bead with Weeps (See Note 5) 1/4"(25mm) gap for drainage (seal with bug screen) Wood Backer Rod Structure & Sealant Sto Textured Finish Sto Primer (Optional - See Note 4) Sto ExtraSeal® Scratch Coat Casing Bead or other Termination Accessory (See Note 5) Flashing Sto ExtraSeal® Skim Coat StoGuard®Conformable Membrane or Sto RapidGuard® Water-Resistive Air Barrier Note: Stop at edges of perforated flange of accessory (See Note 1) (See Note 1)

Notes:

1. Refer to StoGuard Product Use Chart (Table 1.1) for StoGuard detail components; joint treatment, rough opening protection, backing for masonry anchors, or transitions to dissimilar materials, joints and seams in construction.

Detail No.: 65c.15

Date: January 2025

- 2. Refer to General Notes for specific information and design guidance on wall assembly components.
- 3. Stucco scratch and brown coat material in compliance with ASTM C926 and manufactured or listed by Sto Corp.
- 4. Sto Primer is required for Sto Specialty Finishes such as Sto GraniTex, StoSignature Brick, and others. Refer to specific Sto finish product bulletins.
- 5. Components not identified as Sto are furnished by other manufacturers and are not necessarily installed by trades who install the Sto products. Refer to project specific contract documents.

Property of Sto Corp. All Rights Reserved.

Sto products are intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. They should be installed in accordance with those specifications and Sto's instructions. Sto Corp, disclaims all, and assumes no, liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, of for other construction activities beyond Sto's control. Improper use of Sto products or use as part of an improperly designed or constructed larger assembly or building may result in serious damage to Sto products, and to the structure of the building or its components.

STO CORP. DISCLAIMS ALL WARRANTIES EXPRESSED OR IMPLIED EXCEPT FOR EXPLICIT LIMITED WRITTEN WARRANTIES ISSUED TO AND ACCEPTED BY BUILDING OWNERS.

IN ACCORDANCE WITH STO'S WARRANTY PROGRAMS WHICH ARE SUBJECT TO CHANGE FROM TIME. For the fullest, most current information on proper application, clean-up, mixing and other specifications and warranties, cautions and disclaimers, please refer to the Sto Corp. website, www.stocorp.com.



