

StoPowerwall® ExtraSeal® Fixture Attachment


Detail No.: 65c.73
Date: January 2025

Step 1

Apply Sto ExtraSeal® Skim Coat over face of CMU wall to produce a void and pinhole free surface.

Lap StoGuard® Detail Component a minimum 1" (25mm) onto CMU wall and at a distance not to exceed the dimension of the perforated flange of the accessory that surrounds the fixture.

Mark a line around the fixture that will align with the finished wall surface. Lap StoGuard® Detail Component up to this line.



Step 2

Allow StoGuard® Detail Component to dry or cure completely before installing Sto ExtraSeal® Scratch Coat and StoPowerwall® Stucco Brown Coat.

Note: Any excessive or exposed StoGuard® Detail Component that extends outward of sealant may be trimmed, painted or covered by additional finishing products. (e.g. covers, etc.)

Notes:

1. Refer to StoGuard Product Use Chart (Table 1.1) for StoGuard detail components; joint treatment, rough opening protection, backing for masonry anchors, or transitions to dissimilar materials, joints and seams in construction.
2. Refer to General Notes for specific information and design guidance on wall assembly components.
3. Stucco brown coat material in compliance with ASTM C926 and manufactured or listed by Sto Corp.
4. Consult Spray Foam manufacturer for maximum size of gap for product being used.
5. Sto Primer is required for Sto Specialty Finishes such as Sto GraniTex, StoSignature Brick, and others. Refer to specific Sto finish product bulletins.
6. Refer to applicable Sto guide specifications, product bulletins, Tech Hotlines, and other Sto guide details for additional information.
7. Components not identified as Sto are furnished by other manufacturers and are not necessarily installed by trades who install the Sto products. Refer to project specific contract documents.

ATTENTION

Property of Sto Corp. All Rights Reserved.

www.stocorp.com

Sto products are intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. They should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all, and assumes no, liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, of for other construction activities beyond Sto's control. Improper use of Sto products or use as part of an improperly designed or constructed larger assembly or building may result in serious damage to Sto products, and to the structure of the building or its components.

STO CORP. DISCLAIMS ALL WARRANTIES EXPRESSED OR IMPLIED EXCEPT FOR EXPLICIT LIMITED WRITTEN WARRANTIES ISSUED TO AND ACCEPTED BY BUILDING OWNERS IN ACCORDANCE WITH STO'S WARRANTY PROGRAMS WHICH ARE SUBJECT TO CHANGE FROM TIME TO TIME. For the fullest, most current information on proper application, clean-up, mixing and other specifications and warranties, cautions and disclaimers, please refer to the Sto Corp. website, www.stocorp.com.

